



**GENERAL DESCRIPTION:**

Electronic faucet with proximity operation. Vandal-resistant solid brass construction. Operates on DC (battery) or AC permanent power. Water pressure range from 20 to 125 psi. Single inlet 15" flexible stainless steel hose with 3/8" compression fitting for spout connection.

**PRODUCT FEATURES:**

**Vandal-Resistant Brass Body:** Durable - Excellent in high use applications.

**Power Options:**

- **Battery** - Lithium CR-P2 battery. Battery Life - Approx. 200,000 cycles (4 years @ 4,000 cycles per month).
- **Plug-In** - Plug-In - Universal low voltage transformer (80 - 250 VAC, 50 - 60 Hz) with 6 foot long cord. One power supply can run up to 15 faucets and/or flush valves in series.

**Easy and Flexible Installation:**

3-Hole, 4" Centerset installation.  
Water resistant solenoid enclosure mounts to wall.

**Integrated; Easy Service Strainer:**

Patented integrated strainer enclosed in removable debris cup protects the solenoid valve and aerator from debris. Perforated stainless steel strainer is low maintenance and can be easily accessed.

**Temperature Mixing:**

Optional thermostatic mixing valve meets ASSE 1016 performance and anti-scald requirements at 0.5 GPM. Mixing valve will connect directly to solenoid inlet and is housed in matching enclosure.

**Low Lead:**

Complies with CA AB1953 and VT S152.

**MODEL NUMBER:**

- **DC POWERED; single inlet**
  - **6055.205** with cast spout, 0.5 GPM pressure compensating, vandal-resistant spray. Battery included.
  - **6055.202** with cast spout, 1.5 GPM pressure compensating, vandal-resistant aerator. Battery included.
- **AC POWERED; single inlet**
  - **6056.205** with cast spout, 0.5 GPM pressure compensating, vandal-resistant spray. Includes AC power supply (M950169-0070A).
  - **6056.202** with cast spout, 1.5 GPM pressure compensating, vandal-resistant aerator. Includes AC power supply (M950169-0070A).
- **MULTI AC POWERED; single inlet**
  - **6057.205** with cast spout. 0.5 GPM pressure compensating, vandal-resistant spray. One power supply (sold separately) can operate up to 15 faucets in series. 10' extension cable (A922265-0070A) included.
  - **6057.202** with cast spout. 1.5 GPM pressure compensating, vandal-resistant aerator. One power supply (sold separately) can operate up to 15 faucets in series. 10' extension cable (A922265-0070A) included.
- **OPTIONAL Mixing Valve**
  - 605XTMV Thermostatic mixing valve, flex hoses 3/8" compression 20" hose length.

**RECOMMENDED SPECIFICATION**

Electronic Proximity Lavatory shall feature vandal resistant all brass body with single inlet, and in-line strainer. Shall also feature a low energy use electronically operated solenoid valve and microprocessor controlled proximity sensors. Shall meet ANSI A112.18.1 and ANSI 117.1 codes. Fitting shall be American Standard Model # 6055.\_\_\_\_, 6056\_\_\_\_, 6057\_\_\_\_.

## CODES AND STANDARDS

These products meet or exceed the following codes and standards:

**ANSI A117.1**  
**ASME A112.18.1**  
**CSA B 125**  
**NSF 61/Section 9**

 **MEETS THE AMERICANS WITH DISABILITIES ACT GUIDELINES AND ANSI A117.1 REQUIREMENTS FOR ACCESSIBLE AND USABLE BUILDING FACILITIES-CHECK LOCAL CODES**

### Other Aerators Available:

Part Suffix	Description
A15LV	Anti-Microbial 1.5 gpm (5.7 Lpm) Vandal-Resistant Non-Aerated Laminar Flow Outlet
LV15	1.5 gpm (5.7 Lpm) PCA Vandal-Resistant Non-Aerated Laminar Flow Outlet
LV10	1.0 gpm (3.8 Lpm) PCA Vandal-Resistant Non-Aerated Laminar Flow Outlet
V10	1.0 gpm (3.8 Lpm) PCA Pressure Compensating Vandal-Resistant Aerator
V035**	0.35 gpm (1.3 Lpm) PCA Vandal-Resistant Non-Aerated Spray

\*PCA - Pressure Compensating

\*\*Meets Cal Green Code

