

Manual and Metering Faucets

Product Type

Deck Mounted 8" Fixed Centers Concealed Hot and Cold Water Sink Faucet

Features & Specifications

- 8" Fixed Centers
- 5-1/4" Rigid / Swing Gooseneck Spout
- 1.5 GPM (5.7 L/min) Non-Aerating Laminar Outlet
- 4" Wristblade Handle
- Quatum Compression Operating Cartridge
- 1/2" NPSM Supply Inlets and Coupling Nut for 3/8" or 1/2" Flexible Riser
- ECAST® design provides durable brass construction with total lead content equal to or less than 0.25% by weighted average

Performance Specification

- Rated Operating Pressure: 20-125 PSI
- Rated Operating Temperature: 40-140°F

Warranty

- Lifetime Limited Faucet Warranty
- 5-Year Limited Cartridge Warranty
- 1-Year Limited Finish Warranty

Codes & Standards

- ASME A112.18.1/CSA B125.1
- Certified to NSF/ANSI 61, Section 9 by CSA
- California Health and Safety Code 116875 (AB1953-2006)
- Vermont Bill S.152
- NSF/ANSI 372 Low Lead Content
- ADA ANSI/ICC A117.1
- CALGreen

Job Name \_\_\_\_\_

Item Number \_\_\_\_\_

Section/Tag \_\_\_\_\_

Model Specified \_\_\_\_\_

Architect \_\_\_\_\_

Engineer \_\_\_\_\_

Contractor \_\_\_\_\_

☐ Submitted as Shown      ☐ Submitted with Variations

Date \_\_\_\_\_



ECAST

ECAST products are intended for installation where state laws and local codes mandate lead content levels or in any location where lead content is a concern.

## Architect/Engineer Specification

Technical drawing of a three-way gas valve assembly. The drawing includes a side view on the left and a top view on the right. Dimensions are provided in inches and millimeters.

**Side View Dimensions:**

- Horizontal distance from left valve to center: 4 [102]
- Horizontal distance from center to right valve: 4 [102]
- Horizontal distance from left valve to right valve: 8 [203]
- Vertical distance from base to top of valve body: 7-1/2 [191]
- Vertical distance from base to top of riser: 11-5/8 [295]
- Vertical distance from base to top of coupling nut: 4 [102]
- Vertical distance from base to top of valve body: 1-3/8 [35] MAXIMUM WARE THICKNESS
- Horizontal distance from center to top of riser: 5-3/8 [137]
- Horizontal distance from center to top of riser: 3°
- Horizontal distance from center to top of riser: 1-1/4 [32]
- Horizontal distance from center to top of riser: 1-1/8 [29]
- Horizontal distance from center to top of riser: 2-1/4 [57]
- Horizontal distance from center to top of riser: 2-1/4 [57]

**Top View Dimensions:**

- Horizontal distance from left valve to center: 4 [102]
- Horizontal distance from center to right valve: 4 [102]
- Horizontal distance from left valve to right valve: 8 [203]
- Horizontal distance from center to top of riser: 5-3/8 [137]
- Horizontal distance from center to top of riser: 3°
- Horizontal distance from center to top of riser: 1-1/4 [32]
- Horizontal distance from center to top of riser: 1-1/8 [29]
- Horizontal distance from center to top of riser: 2-1/4 [57]
- Horizontal distance from center to top of riser: 2-1/4 [57]

**Labels:**

- 1/2 NPSM COUPLING NUT FOR 3/8 OR 1/2 FLEXIBLE RISER

Last Revision: 07/25/2011 • Date Printed: 04/11/2013 • Product specifications subject to change without notice