


Features

- Unique rimless bowl design
- Uses 20% less water than conventional toilets
- 1.28 gpf / 4.86 lpf low water consumption
- · Round front bowl
- 3" flush valve
- Pilot operated fill valve
- 12" rough-in
- 2" glazed trapway
- Chrome trip lever
- The Mansfield® limited lifetime warranty
- Available in White







Components _____

| Model # | Description | Codes/Standards |
|-----------|---|--|
| 4810-3816 | Round front, two-piece toilet. Less toilet seat and supply. | |
| 4810 | Round front toilet bowl only. Less toilet seat. | HIGH EFFICIENCY TOILET (SETS C) |
| 3816 | Tank and cover only, with left hand, front-mount, chrome trip lever. Less supply. | HIGH EFFICIENCY TOLLET CONTROL OF THE PROPERTY |
| SB100 | Round, toilet seat. Specify color. | |





Specifications

| Model # | Description | Codes/Standards |
|-----------|--|-----------------------|
| 4810-3816 | Round front (1.28 gpf/4.86 lpf) two-piece toilet | C B HEFFCIENCY TOLLET |

| Specification | Description | Specification | Description |
|----------------------|---------------------------------|-----------------|-----------------------------------|
| Material | Vitreous china | Trap Diameter | 2" |
| Water Pressure Range | 20 to 80 PSI | Trap Seal | 2-1/4" |
| Flush System | Gravity fed flushing technology | Rough-in | 12" |
| Water Usage | 1.28 gpf / 4.86 lpf | Shipping Weight | 69.8 lbs. (31.7 kg) |
| Water Surface Area | 6-1/2" X 9-1/4" | Warranty | Vitreous China - Limited Lifetime |
| MaP Rating | 800 grams |] | Tank Trim - Limited One Year |

Technical Information







See our complete line of acrylic and vitreous china bathroom fixtures, plastic tank trim and plumbing products.

These dimensions are nominal and subject to change without notice.

Fixture performance and specifications meet or exceed ASME A112.19.2-2008/CSA B45.1-08 standards, and other state and local codes.