PIONEER ENGINEERING EXCELLENCE Caesar Collection #4CS300T SPECIFICATION SHEET **DESCRIPTION FINISHES** Single Handle Shower Trim Set ٠ PC PVD Polished Chrome Metal Lever Handle BN PVD Brushed Nickel Ceramic Disc Cartridge with . ٠ SS PVD Stainless Steel Temperature Limit Stop PN PVD Polished Nickel Single Function Rain Shower-. GR PVD Golden Rose head 8" Long Shower Arm and Flange Color Match Sleeve and Re-#4CS300T SHOWN * ADA taining Ring STANDARDS APPLICABLE Model #: ASME A112.18.1 ANSI A117.1 FLOW ADA COMPLIANT . Specific Features: Showerhead Limited to 2.5 GPM Project Name: Submitted For: Description Model Finishes #4CS300T Single Handle Shower Trim Set DPC Other____ Required Valve #4020B □ N/A Single Handle Tub and Shower-Valve Set DMSP4CS300T/REV. 12 2012 PIONEER Page 1 of 2 ENGINEERING EXCELLENCE Pioneer:1-800-338-9468 Commerce, CA 90040 www.pioneerind.com

Pioneer Industries, Inc. © 2013

Caesar Collection #4CS300T

SPECIFICATION SHEET

Installation Note:

Please refer to Installation Guide For this Product. Also Please refer to Installation Guide For the Rough-in Valve. Avoid Cross Flow Connections. Do not install a Shut off valve to any of the outlets. Install a 305 MM [12"] Straight Pipe with single elbow for bath between the rough-in valve and the tub spout.

