

Location:



SYMMONS® Degas™

Tub & Shower System S-5402

Specification Submittal



Feature Highlights

- Symmons Tub and Shower System with lever handle
- Symmons Temptrol® pressure-balancing mixing valve with adjustable stop screw to limit handle turn
- Secondary integral diverter/volume control handle
- Showerhead 402SH2, three mode, 7-1/2 inch diameter
- Showerhead arm and flange
- Standard flow rate is 2.5 gpm (9.5 L/min)
Optional lower flow rate restrictor available 
- Tub spout, #542TS
- Polished chrome finish (standard)

Model Numbers

- S-5402
Tub-Shower System with Symmons Temptrol® mixing valve p/n S-4002-BODY
- S-5402-TRM
Trim only, mixing valve ordered separately
- S-4002-BODY
Symmons Temptrol® mixing valve without trim
- S-4002-X-BODY
Symmons Temptrol® mixing valve without trim.
Valve includes integral service stops to allow water shut-off for service

Finish Options / Modifications

Append appropriate -suffix to model number

- STN Satin Nickel
- ORB Oil Rubbed Bronze
- Polished Chrome (standard finish)

Standards / Certifications

ASME A112.18.1-2005/CSA B125.1-05

Options / Modifications

Append appropriate -suffix to model number

- IPS 1/2 inch female IPS connections on Symmons Temptrol® mixing valve
(not available with -X integral service stops)
- X Integral service stops included with Temptrol mixing valve to allow water shut-off for service, p/n S-4002-X-BODY *(option only applies when ordering model S-5402)*
- REV Reverse coring in valve for back to back installations; hot on right, cold on left
(only available with -X integral service stops)
- L/HD Showerhead not included
(includes showerhead arm and flange only)
-  -2.0 2.0 (7.6 L/min) flow rate restrictor
-  -1.5 1.5 (5.7 L/min) flow rate restrictor

Warranty

- Limited Lifetime - to the original end purchaser in consumer installations
- 5 years - for commercial installations

