

▲ Designate Proper Finish Suffix

## BRIZO

# LAVATORY FAUCETS

- Vesi<sup>™</sup> Collection Open Channel Spout
- Ceramic Disc Valving
- Two-Handle Widespread
- 3 Hole Sink Applications
- 6" 16" Centers
- Quick Snap® Installation

#### **STANDARD SPECIFICATIONS:**

- Two-handle lavatory faucets for concealed mounting on 3 hole sinks.
- Widespread 6" to 16" centers.
- Ceramic disc valving.
- Hot and cold stems are interchangeable.
- Solid brass fabricated end valve and spout bodies.
- 1/4 turn stops may be removed for 180° rotation.
- Quick connect hoses and self-locating bases.
- Metal drain has pop-up type fitting with plated flange and stopper.
- Maximum 1.5 gpm flowrate @ 60 PSI.
- Note: Standard mounting deck thickness can be extended 1" with RP10612.

### WARRANTY

- Lifetime Faucet and Finish Limited Warranty to the original consumer purchaser to be free from defects in material and workmanship.
- 5 Year Limited Warranty for usage in all industrial, commercial and business applications.










#### **COMPLIES WITH:**

- ASME A112.18.1 / CSA B125.1
- ASME A112.18.2 / CSA B125.2

Indicates compliance to ICC/ANSI A117.1

- EPA WaterSense
- Verified compliant with .25% weighted average Pb content regulations.



**Delta Faucet Company** 

Indianapolis, Indiana 46280 A Division of Masco Corporation of Indiana © 2009 Masco Corporation of Indiana