

BASEBOARD HEATER DIRECT-VENT

WALL FURNACE

The patented Cozy Gas-Fired, Direct-Vent Baseboard Heater is unique from any other gas heater currently on the market! While fitting in the same spaces as an electric baseboard heater, its operating costs are significantly less expensive. With that innate flexibility and high efficiency, it is a perfect heating solution along any outside wall such as:



NAT.
GAS
& LP

10
YEAR
LIMITED
WARRANTY

- Retrofitting expensive electric baseboard heaters
- Single and multi-family dwellings, high-rise, commercial, manufactured housing and mobile home applications
- Transitional entryways and under-window installations
- Residential additions and sun porch applications
- Supplementing cold-spots
- Or any application where space is at a premium!

**Cozy gas-fired baseboard technology was developed in partnership with three Canadian utility companies. Always consult with your local building code officials prior to install.*

COZY VALUE FEATURES:

- Two Models 5,000 & 9,000 BTU
- 24 Volt Wall Thermostat
- Power Cord
- Ball Valve
- Transistorized, Self-Diagnostic Controls
- Combustion Chamber Warranted for 10 Years
- High Efficient In-Shot Burner
- Sealed Combustion
- Standard Vent Fits Any 4" – 16" Outside Wall Application
- Reliable Direct Spark Igniter
- Requires Only a 2-1/2" Wall Opening
- Up to 3 Units may be Operated in series on 1 wall thermostat
- Flame proving, automatic draft induced control assures maximum efficiency & safety.
- Vent may be installed from the inside for multi-story applications. (See Vent Weather Seal Kit)

COZY



AHRI CERTIFIED®
www.ahridirectory.org

HARDI
Heating, Air-conditioning & Refrigeration Distributors International

Cozy Heating Systems LLC
phone - 502.589.5380
fax - 502.589.5382
www.cozyheaters.com

Made in the USA

BASEBOARD HEATER DIRECT-VENT WALL FURNACE

Cozy



Model #	BBT53	BBT54	BBT103	BBT104
BTU Input / Hr	5,000	5,000	9,000	9,000
Watts	1,485	1,485	2,930	2,930
Type Gas	Nat.	L.P.	Nat.	L.P.
Type Control	24 Volt	24 Volt	24 Volt	24 Volt
AFUE	73.0%	73.0%	80.4%	80.4%
Dimensions WxDxH	48" x 5-3/8" x 9-3/8"	48" x 5-3/8" x 9-3/8"	72" x 5-3/8" x 9-3/8"	72" x 5-3/8" x 9-3/8"
Gas Conn.	3/8"	3/8"	3/8"	3/8"
Voltage	115V	115V	115V	115V
Min. Center of Vent to Floor	7-7/16"	7-7/16"	7"	7"
Wall Opening	2-1/2"	2-1/2"	2-1/2"	2-1/2"
Wall Max Thickness	16"	16"	16"	16"
Wall Min Thickness	4"	4"	4"	4"
Ship Weight	49 lbs	49 lbs	67 lbs	67 lbs

5,000 BTU (Face Off) 48" (122 cm)



9,000 BTU (Face Off) 72" (183 cm)



STANDARD ITEMS

Standard Vent with 1-1/2" I.D. Seal

4"-16" Vent System

Direct Spark Ignition Module Self-Diagnosing

Mounting Template, 24 Volt Wall T-Stat Kit, Power Cord & Ball Valve

OPTIONAL ACCESSORIES

Vent Weather Seal Kit with 2" I.D. Seal

Outside Finish

Inside Finish

Bottom Valve Concealer

Side Valve Concealer

Vent Riser Kit - VRK5/10