

Submitted Model No.: _____

Specific Features: _____



PERSONAL HAND HELD SHOWERS

- Certified Dual Check Valves
- 24" Wall Bar, Wall Mount or Shower Arm Mount

STANDARD SPECIFICATIONS:

- Max 2.50 gpm @ 80 psi, 9.50 L/min @ 552 kPa
- Max 2.00 gpm @ 80 psi, 7.60 L/min @ 550 kPa
- ABS hand held shower with one or three spray patterns – not a positive shut-off
- 69" (1753 mm) flexible plastic hose
- 60"-82" (1524 mm - 2083 mm) stretchable metal hose - 54613 only
- Certified dual check valves for backflow protection
- 24" (610 mm) wall bar with adjustable slide (allows for adjustable shower height) - 54713, 55710, 56713 and 57713 only. Not to be used as a Grab Bar. Not ADA compliant.
- Wall mount bracket - 54510, 54513, 56510, 56513 and 57513 only.
- Shower Mount Bracket - 56613 and 54613.

WARRANTY


- Lifetime Faucet and Finish Limited Warranty to the original consumer purchaser to be free from defects in material and workmanship.
- 5 Year Limited Warranty for usage in all industrial, commercial and business applications.




COMPLIES WITH:

- ASME A112.18.1/CSA B125.1 ♦
- EPA WaterSense®


Spray Patterns



Massage Spray



Full Spray



Soft Drenching Spray

<p>54713</p> <p>24" (610mm)</p> <p>69" (1753 mm)</p> <p>Accepts 1/2" - 14 NPSM Male</p>	<p>56713</p> <p>24" (610 mm)</p> <p>69" (1753 mm)</p> <p>Accepts 1/2" - 14 NPSM Male</p>	<p>55710</p> <p>24" (610 mm)</p> <p>69" (1753 mm)</p> <p>Accepts 1/2" - 14 NPSM Male</p>	<p>57713</p> <p>24" (610 mm)</p> <p>69" (1753 mm)</p> <p>Accepts 1/2" - 14 NPSM Male</p>
<p>54613</p> <p>60"-82" (1524 mm - 2083 mm)</p> <p>69" (1753 mm)</p>	<p>56613</p> <p>69" (1753 mm)</p>	<p>54510</p> <p>69" (1753 mm)</p> <p>Accepts 1/2" - 14 NPSM Male</p>	<p>55510</p> <p>69" (1753 mm)</p> <p>Accepts 1/2" - 14 NPSM Male</p>
<p>54513</p> <p>69" (1753 mm)</p> <p>Accepts 1/2" - 14 NPSM Male</p>	<p>56513</p> <p>69" (1753 mm)</p> <p>Accepts 1/2" - 14 NPSM Male</p>	<p>56510</p> <p>69" (1753 mm)</p> <p>Accepts 1/2" - 14 NPSM Male</p>	<p>57513</p> <p>69" (1753 mm)</p> <p>Accepts 1/2" - 14 NPSM Male</p>

- ◆ Your Delta Faucet hand shower incorporates a backflow protection system that has been tested to be in compliance with ASME A112.18.3 and ASME A112.18.1/CSA B125.1. It incorporates two certified check valves in series, which operate independently and are integral, non-serviceable parts of the wand assembly.



55 E. 111th Street, Indianapolis, Indiana 46280
 350 Edgewood Road, St. Thomas, ON N5P 4L1
 © 2016 Masco Corporation of Indiana

Delta reserves the right (1) to make changes in specifications and materials, and (2) to change or discontinue models, both without notice or obligation. Dimensions are for reference only. See current full-line price book or www.deltafaucet.com for finish options and product availability.

DSP-B-56510 Rev. H