



SPECIFICATIONS

Input Voltage	208-240VAC Single Phase
Kilowatt Rating	20.0
Maximum Amperage	92 AMPS
Water Inlet	3/8" compression
Steam Outlet	1/2" NPT
Drain Pan	3/4" NPT
Safety Valve	3/4" NPT
Electrical Connection	Hardwired

Maximum Room Size (cubic Feet)......650

PRO Series Standard Equipment:

- The only 100% networked digital technology in the industry (all other systems worldwide are old style analog).
- Lifetime Factory Warranty 3 years in-home.
- SmartSteam No irritating temp fluctuations Perfect temp maintenance - Patented
- Fast Start Steam in seconds not minutes Patented
- Auto PowerFlush Pressurized inner tank cleaning system, not a passive gravity drain.
- Stainless Steel drain pan.
- Stainless braided water flex connector.
- Pre-plumbed pop safety valve.

- ½" union to connect to steam line
- Constant steam at a constant rate no cycling.
- Can be plumbed 50 ft. from the shower without upsizing the generator.
- Superior heating elements low watt density.
- Stainless steel construction throughout.
- Power Connection Whip (Approx.45 in.)
- Split tank technology enhances performance and life-span.
- 50 foot keyed water tight data link cable for control.
- Plug & play with ThermaSol Serenity light & music system.
- Drain Pan included

Installation Notes:

Install this generator according to the supplied installation guide. Follow local plumbing and electrical codes. Unit must be accessible.

Generator is factory sized: L x W x H = Cubic Feet. Choose the appropriate generator. For every additional foot of ceiling height over 8 ft, use the next larger generator. Always round up when calculating the total cubic feet.

Compatible options:

- -Signature Control Series
- -Temp-Touch Series
- -Easy Start Series
- -Premium and Deluxe Packages
- -Serenity Light and Music series
- -Serenity Wireless Remote Series



Product Specification:

The steam generator shall be approximately 18.5" x 13.75" x 12" in dimension. The generator shall be made from stainless steel and include: Smart Steam, Fast Start, Auto PowerFlush, Split Tank, and use a 100% networked digital technology.

Shipping Information:

Weight......52 lbs. Length......18 in. Width.....23 in. Height.....14 in. 65

For any further assistance please contact ThermaSol at 800.776.0711 or sales@thermasol.com

Visit www.thermasol.com for a complete product definition





