

Straight Couplings

One End Female National Pipe Thread

74754



A.Y. McDonald Service Fittings are made in the United States of America and are manufactured to meet or exceed the AWWA C800 (latest revision) standard. Our service fittings are rated to withstand the same pressures as the tubing they are designed to fit. They are designed and tested for cold potable water **only**. EPDM rubber gaskets are used in our compression fittings.

Size	Nut	FNPT	74754 Flare x FNPT	74754-22 -22 CTS Compression x FNPT	74754G G CTS Compression x FNPT	74754Q Q CTS Compression x FNPT	74754T T CTS Compression x FNPT
1/2"	1/2"	1/2"	●	●			
1/2" x 3/4"	1/2"	3/4"		●			
3/4"	3/4"	3/4"	●	●	●	●	●
3/4" x 1/2"	3/4"	1/2"	●	●	●	●	●
3/4" x 1"	3/4"	1"	●	●	●	●	●
1"	1"	1"	●	●	●	●	●
1" x 3/4"	1"	3/4"	●	●	●	●	●
1" x 1 1/4"	1"	1 1/4"	●	●	●	●	●
1" x 1 1/2"	1"	1 1/2"	●	●	●	●	●
1 1/4"	1 1/4"	1 1/4"	●	●	●	●	●
1 1/4" x 3/4"	1 1/4"	3/4"		●	●	●	●
1 1/4" x 1"	1 1/4"	1"		●	●	●	●
1 1/2"	1 1/2"	1 1/2"	●	●	●	●	●
1 1/2" x 1"	1 1/2"	1"		●	●	●	●
1 1/2" x 1 1/4"	1 1/2"	1 1/4"		●	●	●	●
2"	2"	2"	●	●	●	●	●
2" x 1 1/2"	2"	1 1/2"		●			●
2 1/2"	2 1/2"	2 1/2"		●			

Size	Nut	FNPT	74754-33 -33 PEP Compression x FNPT	74754-3G -3G PEP Compression x FNPT	74754-3Q -3Q PEP Compression x FNPT	74754-44 -44 PVC Compression x FNPT	74754-55 -55 IP Compression x FNPT
1/2"	1/2"	1/2"				●	
1/2" x 3/4"	1/2"	3/4"				●	
1/2" x 1"	1/2"	1"				●	
3/4"	3/4"	3/4"	●	●	●	●	●
3/4" x 1"	3/4"	1"	●	●	●	●	●
3/4" x 1 1/2"	3/4"	1 1/2"	●	●	●	●	●
1"	1"	1"	●	●	●	●	●
1" x 3/4"	1"	3/4"	●	●	●	●	●
1" x 1 1/4"	1"	1 1/4"	●	●	●	●	●
1 1/4"	1 1/4"	1 1/4"	●	●	●	●	●
1 1/4" x 1 1/2"	1 1/4"	1 1/2"	●	●	●	●	●
1 1/2"	1 1/2"	1 1/2"	●	●	●	●	●
1 1/2" x 3/4"	1 1/2"	3/4"				●	●
1 1/2" x 1"	1 1/2"	1"				●	●
1 1/2" x 1 1/4"	1 1/2"	1 1/4"				●	●
2"	2"	2"	●			●	●
2" x 3/4"	2"	3/4"	●			●	●
2" x 1"	2"	1"	●			●	●

Size	Nut	FNPT	74754-66 -66 Strong Lead Compression x FNPT	74754-67 -67 X Strong Lead Compression x FNPT	74754-68 -68 XX Strong Lead Compression x FNPT
1/2" x 3/4"	1/2"	3/4"			●
5/8" x 3/4"	5/8"	3/4"	●	●	●
5/8" x 1"	5/8"	1"		●	
3/4"	3/4"	3/4"	●	●	●

OPTIONS

- For Handyloc - Replace "Q" or "-3Q" with "H" or "-3H" in 3/4" & 1" only.
- For C903 tube - Replace "Q" with "K". On "Q" Series options only 3/4" x 1" only.
- For valve or fitting less flare nut add "L" to end of model number.
- CTS Anode (QA) & Flare Anode (A) - Replace "Q" with QA or add "A" to flare.
- Insert stiffeners are required on all flexible plastic connections. See page 23.
- See page 15 for Flare conversion adapters.