



Buy it for looks. Buy it for life.®

Specifications

DESCRIPTION

- Metal construction with various finishes identified by suffix
- Includes four round single-function flush mount body sprays
- Includes 7" rainshower showerhead, arm and flange
- Includes four function hand shower with 69" hose assembly, drop ell, vacuum breaker and slide bar
- Includes digital controller for temperature, flow, & spray outlet on/off control

OPERATION

- Digital Thermostatic control
- Digital control dial controls temperature with LED indicators & numeric readout on LCD screen
- Digital control dial controls the flow rate with LED indicators
- Digital on/off button
- Digital pause button
- Digital spray outlet on/off control with graphics on LCD screen
- 4 digital presents for temperature, flow rate, and spray outlet on/off selections
- Temperature range adjustment from 60 degrees F to 120 degrees F (16 degrees C to 49 degrees C). Factory maximum setting is 115 degrees (46 degrees C)
- Body spray face tilts 20 degrees in any direction

FLOW


- Showerhead and handshower limited to 2.5 gpm (9.5 L/min)
- Bodysprays limited to 2.00 gpm (7.6 L/min) each

STANDARDS

- Third party certified to meet ASME A112.18.1/CSA B-125.1 and all applicable requirements referenced therein including ASSE 1016
- Digital controller third party certified to meet UL1951
- Digital controller and Remote control third party certified to meet FCC part 15

WARRANTY

- Lifetime limited warranty against finish defects to the original consumer purchaser
- 5 year warranty against leaks, drips and operation defects to the original consumer purchaser
- 5 year warranty against finish defects if used in commercial installations
- 1 year warranty against leaks, drips and operation defects if used in commercial installations



ioDIGITAL™ 3/4" Vertical Spa

Model: TS296 series, TS3420 series

Optional Remote: SA340 series

(Sold separately)

Valves: (Sold separately)

S3384 ioDigital Vertical Spa Valve

S1300 Body Spray Rough-In Valves (4 required)

