

Capstone®









One Handle Pullout Kitchen

DESCRIPTION

- Metal construction with chrome or stainless finish
- Chrome finish with chrome wand, stainless finish with black wand
- 1/2" IPS connections
- · Six (6) individual boxes per master carton
- · Mounts in single hole or 3 hole installations
- · Pullout spray with metal hose

OPERATION

- · Pivot action, lever style handle
- · Temperature control by 90 degree arc
- Operates in stream or spray mode in the pullout or retracted position
- · Will operate with less than 5 lbs. of torque
- No grasping motion required to operate the faucet handles

FLOW

Aerator limited to 2.2 gpm (8.3 L/min)

CARTRIDGE

· Ceramic disc technology

- o 2.2 gpm (8.3 L/min)
 - 8.406° (213.52 mm)

· Non-metallic, non-ferrous, and brass material

Model: CA40519


· Single body construction for easy replacement

STANDARDS

- Third party certified to CSA B-125.1, ASME A112.18.1, and all applicable requirements referenced therein including NSF61/9
- Contains no more than 0.25% weighted average lead content
- Complies with California Proposition 65 and the Federal Safe Water Drinking Act
- · ADA 🔥 for lever handles
- · Features red/blue hot/cold temperature indicators

WARRANTY - RESIDENTIAL, COMMERCIAL

- Ten year limited warranty against defects in materials and manufacturing workmanship
- Refer to the installation instructions enclosed with each CFG product or call 1-888-450-4910 for complete warranty information



CLEVELAND FAUCET GROUP · 25300 AL MOEN DRIVE · NORTH OLMSTED, OHIO 44070 · (888) 450-5522 · www.cfgonline.com