

Commercial Submittal

• Blades are parallel to shortest dimension · Provides 2-way airflow on one plane

• Available in even sizes up to 36" x 24"

Single Deflection Adjustable Steel Blade Grille (blades parallel to shortest dimension)

· Single deflection surface mount grille with adjustable steel blades

· Nylon bushings on adjustable blades prevent metal on metal rattle · Countersunk mounting holes with color matching Phillips Posidriv screws

Recessed screwdriver operated Opposed Blade Damper (932-0) 2" ADC compliant round collar with bead for ease of installation (square

• Frame dependent on product size, refer to chart below

· Rust resistant pre-coat with durable powder finish

MODEL: 932

• Soft White

Options:

10 x 4

Standard Features:


932 (Extruded Aluminum Frame)




932 (Extruded Aluminum Frame)




932 (Extruded Aluminum Frame)



932 (Stamped Steel One Piece Frame)



932 (Stamped Steel One Piece Frame)



932-O

Additional Information:

Project / Location:

Submittal Notes

Engineer: Architect: Contractor: 18 x 8

	NOMINAL - 3/16	
932 (Stamped	d Steel One Pi	ece Frame)
	NOMINAL + 1 1;	5/16
2	0 0 0 0 0 0	

12 x 8

NOMINAL - 3/16

NOMINAL DUCT

932-O

sizes only) T-20 Tamper Pl	roof Screws				
Finishes: STANDARD COLORS	an Black	re Gray	Aluminum Paint Coffee Tan Warm White Glossy White		
Stamped Steel One Piece Frame Sizes					
6 x 6	10 x 6	12 x 12	14 x 14		
8 x 4	10 x 10	14 x 4	16 x 6		
8 x 6	12 x 4	14 x 6	16 x 8		
8 x 8	12 x 6	14 x 8	18 x 6		

Note: Sizes not shown above use an extruded aluminum surface mount frame with signature line marks.

14 x 10