DRAINS / SILLCOCKS

EVAPORATIVE COOLER PARTS





DIAL P/N	DESCRIPTION		PKG	CTN QTY	CTN WT	
	DRAIN &	OVERFLOW PIPE KIT	ſS			
▲9247	Poly Drain/Smooth Kit		Bag	25	1.8	
▲92475	Poly Drain/Smooth Kit	Slip in, non-threaded overflow pipe, washer, poly drain with 3/4" male garden hose threads.	▲ Bag	25	1.7	
▲9249	Poly Drain/Smooth Kit		Clam	12	1.2	
▲9240	Nylon Drain Kit*	1/2" MPT overflow pipe with flat sided hex head	Bag	25	2.1	
▲92405	Nylon Drain Kit*	for easy install & removal, washer, nylon drain with ½" FPT I.D. and ¾" male garden hose	▲ Bag	25	2.1	
▲9244	Nylon Drain Kit*	threads O.D.	Clam	12	1.6	
▲9243	Nylon Drain Kit*	Same as PN 9240, except with longer overflow pipe for Tradewinds™ Coolers.	Clam	10	1.5	
▲9230	Brass Drain Kit*	Same as PN9240, except with heavy duty brass	Bag	25	3.6	
▲9254	Brass Drain Kit*	drain.	Clam	12	2.5	
	DRAIN	& OVERFLOW PIPES				
▲ 9205	Nylon Cooler Drain*	Nylon drain with $\frac{1}{2}$ " FPT for threaded overflow	Bag	25	1.0	
▲9209		-pipes, male garden hose threads O.D. Washer	Clam	12	0.4	
	Nylon Cooler Drain*	included. Flat sides for all coolers.				
▲9225 ▲92255	Brass Cooler Drain* Brass Cooler Drain*	Same as above except with brass drain.	Bag ▲Bag	25 25	2.8	
▲9229	Brass Cooler Drain*		Clam	12	1.4	
9233	3 ¹ / ₂ " Threaded Overflow Pipe		Bulk	50	1.5	
▲9235	3 ¹ / ₂ " Threaded Overflow Pipe	Threaded ½" MPT standpipe with hex head top,	Bag	25	0.9	
▲92355	3½" Threaded Overflow Pipe	-3½" overall height (½" thread length, 3" smooth length).	▲Bag	25	1.2	
▲9236	3½" Threaded Overflow Pipe	anoon lenguy.	Clam	12	0.5	
9234	4¾" Threaded Overflow Pipe	Same except extra 4¾" in length (½" thread length, 4¼" smooth length).	Bulk	10	0.4	
6951	Rubber Washer for Cooler Drain	1-3/16" rubber washer	Bulk	10	0.04	
		DRAIN AND OVERFLO	N PI	PE		
▲9239	Overflow Drain Assembly*	Prevents overfilling of cooler. Remove for	Bag	10	1.3	
▲92395	Overflow Drain Assembly*	cleaning.	▲ Bag	25	1.9	
▲ 92375	Flat Sided Bushing*	Flat sided plastic drain fitting with rubber washer fits all coolers. Use with Max Cool®	▲Bag	20	0.8	
*2 flat s	ides. Fits Arctic Circle®. Maste	style overflow pipe only. erCool ® and all other coolers.				
	·····	SILL COCKS				
		Nickel plated, ¾" FGH inlet x ¾" MGH outlet				
A 0050		with $\frac{1}{6}$ " FIP side tapped. Fits directly on to	1 - 1 - 1	10	F 0	
▲9250	Sill Cock	existing faucet. Attach angle needle valve or male compression coupling to side tapped 1/4"	Label	12	5.3	
		FIP to connect to cooler. Low lead.				
▲9251	Brass Sill Cock	Brass body, ¾" FGH inlet x ¾" MGH outlet with	Label	12	5.6	
▲92515	Brass Sill Cock	'/' FIP side tapped. Sill cock garden hose thread fits directly onto existing outdoor faucet.	▲ Label	12	5.4	
9252	Brass Sill Cock	Attach angle needle valve or male compression	Bulk	144	60.0	
▲9253	Brass Sill Cock	-coupling to side tapped ½" FIP to connect to	Clam	8	4.3	
▲9257	34" FPT Brass Sill Cock	cooler. Brass body, ¾" FIP inlet x ¾" MGH outlet with	Label	12	5.7	
▲92575	34" FPT Brass Sill Cock	1/8" FIP side tapped. 34" FIP fits directly onto pipe threads. Attach needle valve or male	▲Label	12	4.3	
▲9258	34" FPT Brass Sill Cock	compression coupling to side tapped 1/8" FIP to connect to cooler.	Clam	8	4.3	
▲9520	1/8" MPT Brass Plug (1 per)	Winter seal for Sill Cock.	Clam	10	0.3	
▲9525	1/4" cc Brass Cap (1 per)	Winter seal for Float Valve.	Clam	10	0.2	
		ADDLE VALVES				
9267	1/4" Self Tapping SV		Bulk	200	46.8	
▲9268		Use to run water to cooler. Attaches to copper	_			
	1/4" Self Tapping SV	pipe 3/8" to 1-3/8" O.D. Available w/ rigid self	Bag	25	5.7	
▲92685	1/4" Self Tapping SV	piercing needle.	▲ Bag	25	5.8	
▲9270	1/4" Self Tapping SV		Clam	8	2.2	
9445	1/4" SS Ball Valve & Brass Saddle	Stainless Steel, corrosion resistant, heavy duty -ball valve and brass saddle. Chrome plated.	Bulk	25	7.0	
		•				

Clam

10

3.6

1/4" SS Ball Valve & Brass Saddle Must be pre-drilled.