

# Tubular Brass

## Model 501/502

For most tubs 14" - 16" high

## Model 551/552

For most tubs up to 24" high

**Sturdy 1.5" 17g and 20g Tubular Brass  
Slip-Joint Assembly**

### SPECIFICATIONS

#### FEATURES:

- Metal strainer body for cast iron or plastic tubs
- Designed for heavy-duty use in hotels, motels, rental properties
- Replaceable drip-proof Buna-N-Seal
- Retainer plate for overflow elbow

#### APPROVALS (501/502, 551/552):

- Manufactured in compliance with ASME A112.18.2-2005/CSA B125.2-2005; TIL MSE-051.

#### PATENTS:

- [www.watcomfg.com/patents](http://www.watcomfg.com/patents)

#### THREAD SIZE (STRAINER BODY AND DRAIN ELBOW):

- 1/2" - 11 1/2 NPSM (Coarse Thread)
- 1.865" Major Diameter (outside thread diameter)
- 11.5 threads per inch

**PIPING:**  17g: 501/551 models  20g: 502/552 models

#### OPTIONS:

- Brass Ferrules (add code "-F" to part number)
- Brass Half Ferrules (add code "-HF" to part number)
- New York Lay-Down Tee (add code "-NY" to part number)
- Slip-'N-Solder (no compression slip joints, add Code "-U")
- Special lengths available:
  - Overflow extension (add code "-EXlength") example: -EX6
  - Drain extension (add code "-Dlength") example: -D4



**ADA**

PRESFLO® (PF) and  
Foot Actuated (FA) only

See price list for complete item numbers and available options.

When ordering, please specify complete item number  
and any applicable option codes.

**WATCO**



Always a step ahead

For More Information Contact:  
**WATCO Manufacturing Company**  
1220 South Powell Road  
Independence, MO 64057-2724  
Ph. 816-796-3900 • FAX 816-796-0875  
[www.watcomfg.com](http://www.watcomfg.com)

