

## RCORP3

- Includes RCORP smooth jaw wrench to tighten corp stops without damaging the brass. Corp stop manufacturers recommend smooth jaws to avoid damage from traditional pipe wrench teeth.
- CSK3 socket affixed to handle with slots to fit standard and ball valve corp stop keys.
- Rotate handle end for three different disc slot sizes: 450", .390", .312".

# Smooth Operators



RCORP3 in use

### RCORP SMOOTH JAW WRENCH

- Fits up to 2" corp stops and opens to a generous maximum of 4 1/2"
- Designed to provide quick, easy adjustments to accommodate numerous size changes on the job.
- Smooth jaws are strong, yet gentle on valves and fittings.
- For maximum strength, wrench is forged steel and not a casting.



RCORP #02114

#### CSK3

- Convenient way to reach to open/close corp stops.
- Slide socket slot over key until it stops, then ratchet to open or close the corp stop.
- Rotate socket for 3 different slot sizes: 450", .390", .312".
   Slots fit standard and ball valve corp stop keys.
- Steel construction for strength in a compact size.
- Requires ½" drive wrench.



Wrench not included

## **CORPORATION STOP KEY SOCKETS**

- Universal slot fits most standard corp stops and meter keys in the field.
- Corporation Socket for 3/4" to 2" Corp Stops.
- Uses 1/2" drive ratchet.

#### Catalog Item No. Code

 No.
 Code
 Description

 CSK
 02237
 Steel; Slot Width 0.54"

 L25
 02272
 Cast Iron; Slot Width 0.48"



• Steel construction for strength in a compact size.



Wrench not included.



L25 #02272
• Versatile to fit 1/2" drive wrench or Reed L series

ratchet wrench handles.



Wrench not included.