

PULSER GROUND FAULT LOCATOR



CAT. NO.	UPC NO.	DESCRIPTION
PE2003	08666	Pulser Fault Locator Kit with carrying case
2000H	60357	Transmitter (Includes CH1 & CH2)
2000R	60358	Receiver
AF2	60482	A-Frame
CH1	60360	AC Charger
CH2	60361	DC Charger
59F0002	66216	Battery, Replacement (12V 2.5 Ah)

Product Features:

The Pulser Ground Fault Locator identifies the exact location of even the smallest breaks in insulation by "pulsing" a high-voltage signal that radiates into the earth at the location of the faults. With the A-frame mounted receiver, a visual analog meter points the way to the source of the voltage.

- Multiple faults on a single wire can be identified indicating the need to replace instead of repair.
- Extra-long test leads feature heavy-duty alligator clips for use on multiple cable types.
- Includes a rechargeable transmitter, receiver, A-frame, ground stake, 120V charger and a 12V DC (cigarette lighter) adapter.
- Battery operated (one 12V and one 9V battery included).
- 1-year limited warranty.

Specifications:

Power Requirements	Transmitter: (1) 12V rechargeable battery, Receiver: (1) 9V battery
Battery Life	Transmitter: 23 hours per charge Receiver: 200 hours
Transmitter Power	2400VDC peak
Voltage Protection	40VAC/400VDC
Construction	Transmitter: aluminum housing in polyethylene case, Receiver: powder coated aluminum
Dimensions	Transmitter: 17 in x 8.5 in x 6.5 in (421 mm x 215 mm x 160 mm) Receiver: 33.5 in x 21.75 in x 3.25 in (840 mm x 550 mm x 8 mm)
Weight	12.5 lb complete (5.7 kg)

1390 Aspen Way Vista, CA • 92081

Latin America Phone: 1.760.510.0558 | EMEA Phone: +44 (0) 1633 627710 @2018 Greenlee Inc. • An ISO 9001 Company

EMEA Address: Greenlee Communications Limited • Brecon House, William Brown Close, Cwmbran • NP44 3AB, UK

