

Compact Threading Machines

SUPERTRONIC 2SE / ROPOWER 50R

Portable Compact Threaders

ROTHENBERGER's portable 2" threading machines offer fast and steady, precision threading, cutting, de-burring, and grooving. The powerful 750-watt (1 HP) motor provides strong turning power with consistent torque for swift, effortless production of accurate, standard pipe and bolt threads. The optional foldable, wheeled workbench makes transport easy, whether on site or in the workshop. Replacing the dies is fast and easy due to unique ball-detent feature.

Check out this product on YouTube! Rothenberger USA Channel



- Smooth action impact hammer chuck
Pipes don't slip



- Automatic die head with through-the-head oiling:
Easy to use

- Rear centering chuck:
For axial alignment of the pipe

- Work spindle with closed bearings on both sides:
Low-wear and precise guiding



- Dual-sided tool guide:
Precise guiding

- Ball detent dies:
Quick and easy to change



- Interior deburrer, snap in, 3-blade
Burr-free work

- Sturdy oil pump with high flow power and adjustable fluid quantities, filter system, integrated oil feed:
Optimal lubrication and cooling- No need for external oiler

- Large plastic shavings collection trough:
Easy to clean

Optional

- Wheeled folding stand (00230)



See page 37 for cross reference to RIDGID®* dies

Product Profile

FEATURES

- Motor double insulated:
Work safer
- Stable high torque motor:
Constant power
- Offset spindle lubrication:
Easy to maintain
- Geared oil pump with filter system and adjustable fluid level:
Constant oil flow
- Large plastic chip collection tray:
Easy to clean
- Machine slightly angled:
Reduced oil consumption, oil moistening in pipe interior is avoided
- **Standard jaws and dies will thread with plastic-coated conduit**
- **Can be used on PVC with special dies (2SE)**

TECHNICAL DATA

NPT:	dia. 1/4" - 2"
Motor Strength:	1150 watts (1 HP)
Speed:	40 rpm (No load)
Dimensions:	21" x 17" x 13" (L x W x H)
Weight	97 lbs

SUPERTRONIC 2SE

The SUPERTRONIC 2SE uses quick-change dies with a ball-detent feature that makes aligning replacement dies in the die head fast and easy. The 2SE die head and dies are compatible with the SUPERTRONIC 4SE threading machine.

Standard supply: 2SE machine with automatic die head 1/2"-2" (52500), alloy dies (1/2"-3/4" NPT 89101 and 1"-2" NPT 89102), safety foot switch, set of 4 legs, 1 gallon ROCOOL® oil (01922)

ROPOWER 50R

The ROPOWER 50R uses RIDGID®-compatible dies with the new quick-change ball detent feature. While other manufacturers' RIDGID® style dies may be used in the 50R die head (56265), only ROTHENBERGER's dies snap into position.

Standard supply: ROPOWER 50R, Automatic die head 1/2"-2" (56265), alloy NPT dies (1/2"-3/4" 89162 and 1"-2" 86163), set of 4 legs, safety foot switch, 1 gallon ROCOOL® oil (01922)

*RIDGID® is a registered trademark of Ridge Tool Co.

Description	lb	No.
SUPERTRONIC 2SE with Automatic die head with NPT Alloy dies 1/2" - 2"	97.0	63004
ROPOWER 50R with Automatic die head with NPT Alloy dies 1/2"-2"	97.0	63005
Wheeled stand	70.0	00230
Mounting Kit for ROGROOVER	4.0	56511
Cutter Wheel	0.5	04510