A man is shown from the chest up, standing in a shower. He is holding a white shower curtain with his right hand and looking directly at the camera with a wide-eyed, surprised expression. The shower has white tiled walls and a white shower pan. The lighting is bright and even.

Never run out of
hot water again with
***Electric Tankless
Water Heaters.***



Eemax[™]
Hot Water Solutions Made Easy

HOMEADVANTAGE
Series

HOMEADVANTAGE *Series*



Trust the #1 brand
of electric tankless
water heaters
in the U.S.

 Eemax

HOMEADVANTAGE
Series



Tank vs. Tankless



Function	Continuous heating	Hot water on-demand
Capacity	50 gallons at a time. Decreases over time due to mineral deposits.	Endless hot water. Consistent over life.
Energy Efficiency	90% - 94% efficient	99% efficient
Size	17 cubic ft < 170 lbs	1 cubic ft < 20lbs
Energy Savings \$	n/a	Up to 50%*
Avg. Life	Approx. 10 years	Up to 20 years

* when located at point of use



















A never-ending supply of hot water with never-ending savings.

Eemax tankless electric water heaters activate instantly and deliver an endless supply of hot water at a preset temperature to any point of use with 99% energy efficiency. *

They're small, easy to install and service, and can last up to twice as long as traditional tank water heaters. With the new HomeAdvantage Series you get digital temperature control, "Quick Connect" water connections, advanced styling, and performance you expect.

* dependent on flow rate and incoming water temperature

Choosing the Right HomeAdvantage Product

MODEL	POWER	MAX FLOW	APPLICATIONS	US CLIMATE	# FIXTURES
SS012240T 	11.5 kw	2.5 gpm	Apartments Condos		
SS015240TC 	15 kw	3 gpm	Apartments Condos Small home		
SS019240TC 	19 kw	3 gpm	Apartments Condos		
SS023240TC 	23 kw	3.5 gpm	Apartments Condos Small home		
SS029240T2T 	28.5 kw	4 gpm	Whole home		
SS038240T2T2 	38 kw	6 gpm	Whole home		



Save: water
time
space
energy
money


Need help choosing the right product?

Visit us at eemax.com or call 800-543-6163

 = shower
 = kitchen sink
 = bathroom sink

HOMEADVANTAGE Series

Product Line

						
Description	SS012240T HomeAdvantage	SS015240TC HomeAdvantage	SS019240TC HomeAdvantage	SS023240TC HomeAdvantage	SS029240T2T HomeAdvantage	SS038240T2T2 HomeAdvantage
Color	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel
Warranty						
Parts	Limited 1 year	Limited 1 year	Limited 1 year	Limited 1 year	Limited 1 year	Limited 1 year
Leaks	Limited 5 year	Limited 5 year	Limited 5 year	Limited 5 year	Limited 5 year	Limited 5 year
Unit Configuration						
No. of Chambers	1	2	2	2	3	4
Voltage	240	240	240	240	240	240
Power (KW)	11.5	15	19	23	28.5	38
Amperage	48	64	80	96	120	160
Circuits Required	1 x 50A	2 x 40A	2 x 40A	2 x 50A	3 x 40A	4 x 40A
Recommended Wire Size	1 x 6/2 AWG	2 x 8/2 AWG	2 x 8/2 AWG	2 x 6/2 AWG	3 x 8/2 AWG	4 x 8/2 AWG
Turn-on for First Stage (gpm)	0.7	0.7	0.7	0.7	0.7	0.9
Max flow (gpm)	2.5	3	3	3.5	4	6
Water Connections	3/4"	3/4"	3/4"	3/4"	3/4"	3/4"
Factory Default Set Temp (Thermostatic)	140°F	140°F	140°F	140°F	140°F	140°F
Temperature Rises at 240VAC						
Temp Rise at 1.50 gpm (F)	52	68	87	105	135	100
Temp Rise at 2.00 gpm (F)	39	51	65	79	133	132
Temp Rise at 2.50 gpm (F)	31	41	52	62	76	103
Temp Rise at 3.00 gpm (F)		34	43	52	65	86
Temp Rise at 4.00 gpm (F)					49	65
Temp Rise at 5.00 gpm (F)						52
Temp Rise at 6.00 gpm (F)						43
Features						
LED Temp. Display with adjustment	Yes	Yes	Yes	Yes	Yes	Yes
Water & Electrical Connections (Top/Bottom)	Bottom	Bottom	Bottom	Bottom	Bottom	Bottom
Water Connection: "Quick Connect"	Yes	Yes	Yes	Yes	Yes	Yes

Featuring...

Digital Temperature Control:

HomeAdvantage adjusts the power applied to its heating modules to maximize energy savings by sensing inlet water temperature and flow rate.

Easy Temperature Selection:

HomeAdvantage makes it easy to adjust your exact comfort setting with finger-tip control pad and temperature LED display. Range 100°F to 140°F.

Easy "Quick Connect" Water Fittings:

Fast installation. No soldering.



Eemax, Inc.
800-543-6163

eemax.com

353 Christian Street
Oxford, CT 06478

