

Digital Vacuum Micron Gauge

DMG150 UPC: 053533507720

Functions

- Measures in microns, pascals, Millibar, mmHg, mTorr
- Range: 0 to 15,000 microns
- Maximum over pressure 700 PSI
- Ambient temperature measurement

Features

- 5 units of measurement
- Real time leak measurement
- Time period leak measurement
- Backlit display

- Instant warm up time
- Instant response time
- Sensor fail detection
- Low battery indicator
- Sleep mode
- Compact and lightweight

Includes

45 degree coupler
Battery (CR123A)
Manual (17393)

Warranty

1-Year limited warranty

Support materials

Manual: 17393
Data sheet: L416



Dual AC Operation Hermetic Compressor Analyzer

HA1 UPC: 053533500752

Functions

- Dual voltage operation of 120V/240V AC
- 3 ranges of 250V AC starting capacitors between 88 and 301 MFD

Features

- Indicates continuity and ground faults in motor windings with LED lights
- Free locked rotors by reversing motor action

Includes

Adapter cord (ACF1)
Manual (HA1-MAN)

Warranty

1-Year limited warranty

Support materials

Manual: HA1-MAN
Data sheet: L351



**USA
ONLY**

Refrigerant Leak Detector w/ Gooseneck

RLD10 UPC: 053533503937

Functions

- Sensitive to .5 ounce per year R134A, R123, R410A
- Automatically detects all existing halogenated refrigerants and blends

Features

- Two position sensitivity selector
- Audible tick and visual indicators identify refrigerant leak rate

- Auto zeros when turned on
- 18 1/2 inch long gooseneck probe
- Colored LED leak indication

Includes

Battery (9V)
Manual (RLD10-MAN)

Warranty

1-Year limited warranty

Support materials

Manual: RLD10-MAN
Data sheet: L351



Refrigerant Leak Detector w/ Solid Electrolyte Sensor

RLD15B UPC: 053533507430

Functions

- Detects industry standard refrigerants including, but not limited to: HFC, HCFC, CFC (R134A, R410A)
- Hydrocarbon blends: HC-12a, OZ-12a

Features

- Solid electrolyte semiconductor sensor technology
- Digital numeric leak size indicator
- 3 Sensitivity levels
- Visual LED leak alarm

- Automatic calibration and ambient level reset
- Splash resistant
- Worklight
- Hard carrying case

Includes

Sensor filters 5 (RLDTF)
Leak test vial (RLDLS)
Batteries 4 (AA)
Hard carrying case
Manual (17203)

Warranty

2-Year limited warranty

Support materials

Manual: 17203
Data sheet: L400

