



# Refrigerant Leak Detector

## A2L Certified



### Functions

- Detects industry standard refrigerants

### Features

- A2L Certified
- Solid electrolyte semiconductor sensor
- Digital numeric leak size indicator
- 3 Sensitivity levels
- Visual LED leak alarm
- Automatic calibration & ambient level reset
- Splash resistant
- Worklight
- 2-Year limited warranty

### Applications

Ensuring system is installed and setup properly  
Verifying that system connection seals are still working and not wearing down  
Finding leaks is the first step in preventing costly damage  
Confirm that local and state level laws and guidelines are being met





### Includes

- Sensors filters 5 (RLDTF)
- Leak test vial (RLDLS)
- Batteries 4 (AA)
- Hard carrying case
- Manual

### Specifications

<b>Sensitivity</b>	.05 oz/yr R134a .025 oz/yr R22
<b>Sensor Life</b>	> 300 Hours
<b>Response Time</b>	≤1sec
<b>Power Supply</b>	4 (AA) Alkaline
<b>Battery Life</b>	4 - 6 Hrs. Continuous
<b>Warm-Up Time</b>	<20 Seconds
<b>Probe Length</b>	17 inches
<b>Numerical Display</b>	7 Segment Digital (1-9)
<b>Display Refresh Rate</b>	3/sec.
<b>Operating Temperature</b>	-24 to 125°F (-31 to 52°C)
<b>Operating Humidity</b>	<95% non-condensing
<b>Operating Altitude</b>	<10,000 ft.
<b>Storage Temperature</b>	-4 to 122°F (20 to 50°C)
<b>Pollution Degree</b>	4
<b>Weight, lbs</b>	1.5 Lbs
<b>Certifications</b>	SAE J2791, SAE J2913 (A2L Certified) EN14624-2012 ASHRAE 173-2012
<b>Warranty</b>	2-Year limited warranty

