

SA-SPM 6 control boxes

Application

SA-SPM 6 control boxes are used as starting units for single-phase, 3-wire motors ranging from 0.5 Hp to 5 Hp (.37 kW to 3.7 kW).

SA-SPM 6 from 1.5 Hp to 5 Hp (1.1 kW to 3.7 kW) is available in two versions, standard and deluxe.

The standard version incorporates a motor -protective circuit breaker and thus protects the motor against overload.

The deluxe version is identical to the standard version with the following addition a motor contactor is included for connection and disconnection of the power supply.

Technical data

Enclosure class: IP42.

Ambient temperature: -4 °F to +140 °F
(-20 °C to +60 °C).

Relative humidity: Maximum 95 %, normal non-aggressive atmosphere.

SA-SPM 6 control box part numbers

Version	Single phase	Volts		[Hp]					Product number	
		115 V	230 V	.5	.75	1	1.5	2		3
Standard	•	•		•						98315240 98821580
Standard	•		•	•						98315251 98821631
Standard	•		•		•					98315252 98821632
Standard	•		•			•				98315253 98821633
Standard	•		•				•			98315254
Deluxe	•		•				•			98315255
Standard	•		•					•		98315256
Deluxe	•		•					•		98315257
Standard	•		•						•	98315258
Deluxe	•		•						•	98315259
Standard	•		•						•	98315260
Deluxe	•		•						•	98315261



TMD3 8150 0607

Fig. 74 SA-SPM 6 control box