The Model 26 and B26 are field testable, backflow protected wall faucets intended for irrigation purposes in mild climate areas. The Model B26 is enclosed in a wall mounted box. Both models are designed to blend with modern architecture for installation on or in homes, service stations, churches, motels, drive-in restaurants, etc. The Model Y26 is designed to be used on a stand pipe in the lawn and garden, etc.

SPECIFICATIONS:

MODEL 50HF BACKFLOW PREVENTER -

Patent Pending

- ASSE 1052 Approved
- Listed by IAPMO
- Field Testable
- Two Independent Check Valves
- · Drains automatically when hose is removed
- · No spray back

FEATURES:

EPDM PACKING: Prevents leaking.

PACKING NUT: Adjustable brass nut with deep stem

guard.

VALVE SEAT: Standard "O" size washer.

HANDLES: Furnished with polycarbonate wheel handle

and loose tee key. Optional: Metal wheel handle.

INLETS: Model 26 as shown below.

Model B26: 26P- ½ or 26P ¾ only.

Model Y26: ¾ " FPT.

MAX PRESSURE: 125 p.s.i.

MAX TEMPERATURE: 120° F

SHIPPING WEIGHT: (per unit)

MODEL 26 & Y26: 1.2 lbs

MODEL B26: 14.6 lbs (brass or chrome box)

6.5 lbs (aluminum box)

Inlet Descriptions

MODEL 26/B26

P-½ Inlet ½" FPT P-¾ Inlet


P-% Inlet 34" FPT

MODEL 26 ONLY CP Inlet

COMBINATION
1/2" COPPER TUBE
1/2" MPT

MODEL 26 ONLY

C Inlet COMBINATION 1/2" COPPER TUBE 3/4" COPPER TUBE



For Installation / Troubleshooting Instructions go to www.woodfordmfg.com or call 1-800-621-6032

Wall Faucets



Model 26/B26/Y26



Exterior Finish:
Standard - Chrome
Optional- Rough Brass (BR) or Polished Chrome (PC)



Exterior Finish:
Standard - Chrome
Optional- Rough Brass (BR) or Polished Brass (PB)
Other Options: Anodized Aluminum Box and Door



Exterior Finish:
Standard - Chrome
Optional- Rough Brass (BR) or Polished Chrome (PC)

©2012 WOODFORD Mfg. Rev. 02/12 Form No. 26.109