

CORDLESS POWER TOOL ACCESSORIES

Recipro Saw Blades

for Model BJR141Z / BJR181Z / BJR182Z

Length	TPI	Width	Thickness	Material	Type	Application	2/Pkg.	
Metal Cutting	4"	14	5/8"	.031"	HSS	Straight Back	Pipe, conduit, channel, metals from 3/16" - 1/4"	723019-G-2
	4"	18	5/8"	.031"	BIM	Straight Back	Heavy gauge metal 1/8" - 3/16", hard rubber	723017-H-2
	4"	24	5/8"	.031"	BIM	Straight Back	Pipe, conduit, channels, thin gauge metal from 18 gauge to 1/8"	723017-J-2
	6"	14	5/8"	.031"	BIM	Straight Back	Pipe, conduit, channel, metal from 3/16" - 1/4"	723017-B-2
	6"	14	5/8"	.031"	HSS	Straight Back	Pipe, conduit, channel, metal from 3/16" - 1/4"	723019-A-2
	6"	18	5/8"	.031"	BIM	Straight Back	Heavy gauge metal 1/8" - 3/16", hard rubber	723017-C-2
	6"	18	5/8"	.031"	HSS	Straight Back	Heavy gauge metal 1/8" - 3/16", hard rubber	723019-C-2
	6"	24	5/8"	.031"	BIM	Straight Back	Pipe, conduit, channel, thin gauge metal from 18 gauge to 1/8"	723017-D-2
	6"	24	5/8"	.031"	HSS	Straight Back	Pipe, conduit, channel, thin gauge metal from 18 gauge to 1/8"	723019-D-2

Length	TPI	Width	Thickness	Material	Type	Application	2/Pkg.	
All-Purpose	6"	10	5/8"	.031"	BIM	Straight Back	Metal, bar & pipe over 1/4", nail embedded wood	723017-A-2
	6"	10	5/8"	.031"	HAS	Straight Back	Metal, bar & pipe over 1/4", nail embedded wood	723018-D-2

HCS High Carbon Steel	Lasts 10x Longer than HCS blades
BIM. Bi-Metal	
HSS High Speed Steel	Dure 5 fois plus than HCS blades

Blade Thickness	Application
.035"	Flexible & standard
.050"	Heavy duty
.062"	Demolition

Material	TPI	Application
WOOD	3	Very fast, rough Combination - fast/clean Fast, rough
	Progressive 6	
ALL-PURPOSE	10	Rough - heavy wood with nails Combination - fast/clean Aggressive - soft metal Fast, heavy metal
	Progressive 8/12	
	10/14	
METAL	10	1/4" + thick Combination - all thicknesses 3/16" - 1/4" thick 1/8" - 3/16" thick -1/8" thick
	Progressive 14	
	18	
	24	

6 Piece Assortment Pack

Description

6 Pc. Bi-Metal Pack - (1) each:

- 723054-A (6 TPI)
- 723064-A (10TPI)
- 723066-A (18 TPI)
- 723061-A (18 TPI)
- 723079-A (Progressive)
- 723080-A (Progressive)

Part # 723086-A-A

3 Piece Assortment Packs

Description

3 Pc. Bi-Metal Pack - (1) each:

- Wood (9 TPI)
- Metal/Wood (18 TPI)
- Metal (24 TPI)

Part # 193572-3

Description

3 Pc. HCS, HSS, HAS Pack - (1) each:

- 723018-A (6 TPI)
- 723018-D (10 TPI)
- 723019-C (18 TPI)

Part # 723016-3-A

Recipro Saw Blades

for Model 4390DW



Blade Length	Teeth Per Inch	Tool model	Usage	5 Pack
4"	24	4390D/DW	for mild steel, plastics, masonite, formica, plywood	792542-5
5-7/8"	24	4390D/DW	for mild steel, plastics, masonite, formica, plywood	792615-4
4-3/4"	9	4390D/DW	for wood - thin kerf design	792541-7
5-7/8"	9	4390D/DW	for wood - thin kerf design	792616-2

Circular Saw Blades



BLADE DIAM.	BORE	TEETH	APPLICATION	GRIND	KERF	MAX RPM model #	FOR MODELS	PART #
3-3/8"	5/8" / 16 mm	20 C/T	hard and soft wood - rip	ATB	ultra thin kerf .039	2240	5094DWD	792623-5
3-3/8"	5/8" / 16 mm	50 steel	hard and soft wood - general purpose	N/A	thin kerf .046	2240	5094DWD	721003-8
3-3/8"	5/8" / 16 mm	50 steel	plywood	N/A	ultra thin kerf .031	2240	5094DWD	792299-8
5-3/8"	5/8" / 16 mm	30 C/T	non ferrous metal - general purpose	TCG	thin kerf .039	4500	BCS550Z / BSS500Z	A-94518
5-3/8"	5/8" / 16 mm	50 C/T	thin metals - mild steel	ATB	thin kerf .039	4500	BCS550Z / BSS500Z	A-94524
6-1/4"	5/8" / 16 mm	30 C/T	hard and soft wood - rip	ATB	thin kerf .062	4770	5036DWD / 5046DWD	792365-1
6-1/4"	5/8" / 16 mm	40 C/T	fiber cement board	ATB	thin kerf .059	4770	5036DWD / 5046DWD	A-90700
6-1/4"	5/8" / 16 mm	46 C/T	non ferrous metal / coated - general purpose	TCG	thin kerf .063	4770	5036DWD / 5046DWD	A-90685
6-1/4"	5/8" / 16 mm	56 C/T	non ferrous metal - general purpose smooth cut	TCG	thin kerf .063	4770	5036DWD / 5046DWD	A-90691
6-1/2"	5/8" / 16 mm	24 C/T	hard and soft wood - smooth cut - cross cut	ATB	thin kerf .059	4770	BSS611X / BSS610X2	A-90716
6-1/2"	5/8" / 16 mm	24 C/T	hard and soft wood	ATB	thin kerf .059	4770	BSS611X / BSS610X2	A-85092

Diamond Blades

Diamond Blades for longer lasting cuts in masonry-type materials.

Blade Diameter	Arbor		Max RPM	Part #
3-3/8" (85 mm)	5/8" (16 mm)	For general purpose wet cutting tile and glass.	2,240	724950-8C
3-3/8" (85 mm)	5/8" (16 mm)	Wet/Dry, for stone masonry and gen. purpose.	17,984	724950-8A
3-3/8" (85 mm)	5/8" (16 mm)	Wet/Dry for gen. purpose (bulk)	17,984	724950-8A-X
3-3/8" (85 mm)	5/8" (16 mm)	Wet cutting continuous rim	1,300	A-01323

Circular Saw Legend

- ATB - Alternate Top Bevel
- FT - Flat Top
- TCG - Triple Chip Grind
- HG - Hollow Ground
- FTG - Flat Top Grind

Cordless Power Tools