

Makita®



Celebrating
100 YEARS
of Innovation



LXT
LITHIUM-ION

BRUSHLESS

XPH07T

18V LXT® BRUSHLESS 1/2"
HAMMER DRIVER-DRILL

1,090 In.Lbs OF AWESOME

See page 12

AVT®
Anti Vibration Technology



HR4013C

1-9/16" AVT® ROTARY HAMMER

Advanced Anti-Vibration Technology for up to 3X Less Vibration
See page 31

makitatools.com

NEW XPH07M/T/Z

18v LXT® Brushless 1/2" Hammer Driver-Drill Kit



5.0Ah
45 Minute
Charge Time

1,090 IN. LBS. **OF AWESOME**

NEW XSF03M/Z

18v LXT® Lithium-Ion Brushless Drywall Screwdriver



PUSH DRIVE



Push Drive™ Technology – in lock-on mode, the motor starts only when the fastener is engaged to save battery power and reduce noise

4.0Ah
40 Minute
Charge Time

WORK ALL DAY

NEW XDT09M/Z

18v LXT® Lithium-Ion Brushless Quick-Shift Mode™ 3-Speed Impact Driver



SMALLEST MOST POWERFUL IMPACT DRIVER YET

NEW XST01M/Z

18v LXT® Lithium-Ion Brushless Oil-Impulse 3-Speed Impact Driver



OIL-IMPULSE™
Lower Noise for Quiet Operation

NEW XWT02M/Z

18v LXT® Lithium-Ion Brushless 1/2" 3-Speed Impact Wrench



3-SPEED
210 FT. LBS. OF MAX TORQUE

BL MOTOR BRUSHLESS

Makita-Built BL™ Brushless Motor
Delivers increased motor efficiency to provide up to 50% longer battery life per charge



UP TO **50%**
LONGER
RUN TIME

INCREASED
POWER & SPEED

LONGER LIFE
BRUSHLESS MOTOR

UNPLUG THE CORD

4.0Ah BATTERY



LXT
BRUSHLESS
PUSH(DRIVE)

NEW XSF03M

XSF03Z Tool Only

18v LXT® BRUSHLESS DRYWALL SCREWDRIVER KIT

Drives 1,860 Screws On A Single Charge with Push Drive™ Technology**

- BL™ Motor delivers 0-4,000 RPM to handle a variety of drywall and framing applications
- Push Drive™ Technology – in lock-on mode the motor starts only when the fastener is engaged for a quieter work environment and to save battery power
- Ergonomically designed rubberized pistol grip with large 2-finger trigger for increased comfort

PUSH(DRIVE)



In lock-on mode, the motor starts only when the fastener is engaged to save battery power and reduce noise

WORK ALL DAY



Model XSF03M Includes: 2 ea. 4.0 Ah Battery (BL1840), Rapid Optimum Charger (DC18RC), Tool Case
Model XSF03Z Includes: Tool only - battery and charger not included

Hex Shank	1/4"
No Load Speed	0 - 4,000 RPM
Battery	18v LXT® Lithium-Ion 4.0 Ah
Overall Length	9-7/8"
Net Weight (w/battery)	3.8 lbs.
Shipping Weight	12.4 lbs.

* 4.0 Ah battery will hang up to 40 sheets of 4x8 1/2" Drywall. 1-1/4" (32mm) screw into .59" (15mm) drywall into 20 gauge (1.0mm) steel stud using Push Drive™

**1-1/4" (32mm) screw .59" (15mm) drywall into 20 gauge (1.0mm) steel stud

4.0Ah BATTERY



NEW XOC01M

18v LXT® CUT-OUT TOOL KIT

Slim Body Design (2-1/4") for Comfort and Control

- Makita-built motor delivers 30,000 RPM for fast cutting
- Weighs only 3.7 lbs. with battery for reduced operator fatigue
- Quick and easy "tool-less" depth adjustment
- On board bit change capabilities eliminates need for wrench
- Large and conveniently located shaft lock button for fast bit changes
- Accepts both 1/8" and 1/4" bits

Model XOC01M Includes: 2 ea. 4.0 Ah Battery (BL1840), Rapid Optimum Charger (DC18RC), Spanner Wrench (781008-0), 2 ea. 1/8" Drywall Guide Point Bit (193446-8), Tool bag
Model XOC01Z Includes: Tool only - battery and charger not included

Collet Capacity	1/8", 1/4"
No Load Speed	30,000 RPM
Battery	18v LXT® Lithium-Ion 4.0 Ah
Overall Length	12-3/8"
Net Weight (w/battery)	3.7 lbs.
Shipping Weight	11 lbs.



XRF01

18v LXT® AUTOFEED SCREWDRIVER KIT

Ideal for Decking and Subfloors

- Makita-built 4-pole motor delivers superior fastening speed with 4,000 RPM for decking and sub-floor applications
- High collated screw capacity range: 1-3/4" to 2-15/16"
- Screw guide prevents screw tangling and can fold against the autofeed housing for easy storing
- Rugged aluminum dust-proof autofeed housing provides smooth sliding action
- Compact and ergonomic design at only 18-1/4" long

Model XRF01 Includes: 2 ea. 3.0 Ah Battery (BL1830), Rapid Optimum Charger (DC18RC), Tool Bag
Model XRF01Z Includes: Tool only - battery and charger not included

Bit Type	1/4" Hex
Collated Screw Capacity	1-3/4" - 2-15/16"
No Load Speed	4,000 RPM
Battery	18v LXT® Lithium-Ion
Overall Length	18-1/4"
Net Weight (w/battery)	5.2 lbs.
Shipping Weight	14.8 lbs.



XTS01

18v LXT® 3/8" CROWN STAPLER KIT

Contact Actuation for Production Environments

- Makita-built motor delivers power to fasten a wide range of 3/8" crown staples (lengths 1/4", 3/8", 1/2", 5/8", 3/4" & 7/8"); also utilizes Arrow™ T50
- A convenient window on magazine shows the number of remaining staples
- Spring-loaded driving mechanism allows for a more compact tool with less weight
- Contact actuation is well-suited for production environment

Model XTS01 Includes: 2 ea. 3.0 Ah Battery (BL1830), Rapid Optimum Charger (DC18RC), Tool Bag
Model XTS01Z Includes: Tool only - battery and charger not included

Staple Width	3/8"
Leg Length	1/4" to 7/8"
Crown	3/8"
Staple Magazine Capacity	98 staples
Battery	18v LXT® Lithium-Ion
Overall Length	9-7/8"
Net Weight (w/battery)	5.3 lbs.
Shipping Weight	14.2 lbs.



NEW XGC011

18v LXT® 10 OZ. CAULK/ADHESIVE GUN KIT

Delivers an Industry-Leading 1,100 lbs. of Dispensing Force

- Makita-built motor delivers 1,100 lbs. of dispensing force to dispense the highest viscosity adhesives and sealants
- 5 speed dial optimizes flow rate from 0-66 IPM
- Variable speed trigger allows user match speed to the application
- Drip-reduction feature automatically relieves pressure to the material when trigger is released to prevent unintentional dispensing

Model XGC011 Includes: 1 ea. 3.0 Ah Battery (BL1830), Rapid Optimum Charger (DC18RC), Tool Bag
Model XGC01Z Includes: Tool only - battery and charger not included

Capacity (caulk or sealants)	10 oz.
Dispense Force	1,100 lbs.
Inches Per Minute	0 - 66 IPM
Speed Settings	5
Battery	18v LXT® Lithium-Ion
Overall Length	15-7/8"
Net Weight (w/battery)	5.1 lbs.
Shipping Weight	14.8 lbs.



NEW XGC011B

18v LXT® 20 OZ. CAULK GUN KIT

Delivers Up To 2.5X More Dispensing Speed

- Makita-built motor delivers 1,100 lbs. of dispensing force to dispense the highest viscosity adhesives and sealants
- 5 speed dial optimizes flow rate from 0-66 IPM
- Variable speed trigger allows user match speed to the application
- 360° rotatable cartridge holder fits 20 oz. cartridges, sausage packs and bulk caulk and adhesives

Model XGC011B Includes: 1 ea. 3.0 Ah Battery (BL1830), Rapid Optimum Charger (DC18RC)
Model XGC01ZB Includes: Tool only - battery and charger not included

Capacity (caulk or sealants)	20 oz.
Dispense Force	1,100 lbs.
Inches Per Minute	0 - 66 IPM
Speed Settings	5
Battery	18v LXT® Lithium-Ion
Overall Length	21-1/4"
Net Weight (w/battery)	6 lbs.
Shipping Weight	16 lbs.

Flashlights



L.E.D. Flashlight
LXLMO4

Run time: Up to 13 hours**



Xenon Flashlight
BML185

Run time: Up to 4.3 hours**
Replacement bulb: A-90261



L.E.D. Flashlight
LXLMO3

Run time: Up to 22 hours**



Fluorescent/Incandescent Flashlight
BML184

Run time: Up to 4 hours**
Replacement bulb: SM0000050

L.E.D. Flashlight
LXLMO1

Run time: Up to 50 hours**



* Battery & Charger not included

** With BL1830 Battery



6,000RPM

FS6200 / FS6200TP



6,000 RPM DRYWALL SCREWDRIVER

Precision Balance with Less Weight

- Powerful 6.0 AMP motor with 0-6,000 RPM to handle the most challenging applications
- Less weight (only 3.0 lbs.) with precision balance for ultimate user comfort
- Built-in LED light illuminates the work area for greater productivity in low-light applications
- Steel-reinforced belt clip for user convenience and increased durability

Model FS6200 Includes: 3" Magnetic Bit Holder (784801-1), #2 Phillips Insert Bit, 1", 10/pk (784211-B)

Model FS6200TP features 50 ft. Cord with Twist Lock

Bit Type	1/4" Hex
No Load Speed	0 - 6,000 RPM
AMPS	6
Overall Length	11-1/8"
Net Weight	3 lbs.
Shipping Weight	4.4 lbs.



4,000RPM

FS4200 / FS4200A / FS4200TP



4,000 RPM DRYWALL SCREWDRIVER

Precision Balance with Less Weight

- Powerful 6.0 AMP motor with 0-4,000 RPM to handle the most challenging applications
- Less weight (only 3.0 lbs.) with precision balance for ultimate user comfort
- Built-in LED light illuminates the work area for greater productivity in low-light applications
- Steel-reinforced belt clip for user convenience and increased durability

Model FS4200 Includes: 3" Magnetic Bit Holder (784801-1), #2 Phillips Insert Bit, 1", 10/pk (784211-B)
Model FS4200A feature 50 ft. Cord
Model FS4200TP feature 50 ft. Cord with Twist Lock

Bit Type	1/4" Hex
No Load Speed	0 - 4,000 RPM
AMPS	6
Overall Length	11-1/8"
Net Weight	3 lbs.
Shipping Weight	4.4 lbs.



2,500RPM

FS2200



2,500 RPM DRYWALL SCREWDRIVER

Precision Balance with Less Weight

- Powerful 6.0 AMP motor with 0-2,500 RPM to handle the most challenging applications
- Less weight (only 3.5 lbs.) with precision balance for ultimate user comfort
- Built-in LED light illuminates the work area for greater productivity in low-light applications
- Steel-reinforced belt clip for user convenience and increased durability

Model FS2200 Includes: 3" Magnetic Bit Holder (784801-1), #2 Phillips Insert Bit, 1", 10/pk (784211-B)

Bit Type	1/4" Hex
No Load Speed	0 - 2,500 RPM
AMPS	6
Overall Length	11-1/8"
Net Weight	3.5 lbs.
Shipping Weight	5 lbs.



3706

DRYWALL CUT-OUT TOOL

Slim Body Design (2-1/4") for Comfort and Control

- Powerful 5 AMP motor for cutting into various material
- 32,000 RPM for fast cutting
- 2-way "Slide and Bump" on/off switch
- Sealed switch for extra protection from dust and debris and longer tool life
- "Tool-less" depth adjustment sets the desired cutting depth quickly and easily

Model 3706 Includes: Spanner Wrench (781008-0), 1/4" Collet (763608-8), 1/8" Collet (763660-6), 2 pc. 1/8" Drywall Guide Bit

Collet Capacity	1/8", 1/4"
No Load Speed	32,000 RPM
AMPS	5
Overall Length	9-7/8"
Net Weight	2.4 lbs.
Shipping Weight	3.1 lbs.



PUSH(DRIVE)

LXT BRUSHLESS

NEW XSF03M 18v LXT® BRUSHLESS DRYWALL SCREWDRIVER KIT

- BL™ Motor delivers 0-4,000 RPM to handle a variety of drywall and framing applications
- Push Drive™ Technology – in lock-on mode the motor starts only when the fastener is engaged for a quieter work environment and to save battery power
- Ergonomically designed rubberized pistol grip with large 2-finger trigger for increased comfort



NEW XOC01M

18v LXT® CUT-OUT TOOL KIT

- Makita-built motor delivers 30,000 RPM for fast cutting
- Weighs only 3.7 lbs. with battery for reduced operator fatigue
- Quick and easy "tool-less" depth adjustment
- On board bit change capabilities eliminates need for wrench
- Large and conveniently located shaft lock button for fast bit changes
- Accepts both 1/8" and 1/4" bits

Model XOC01M Includes: 2 ea. 4.0 Ah Battery (BL1840), Rapid Optimum Charger (DC18RC), Spanner Wrench (781008-0), 2 ea. 1/8" Drywall Guide Point Bit (193446-8), Tool bag

Model XOC01Z Includes: Tool only - battery and charger not included

Collet Capacity	1/8", 1/4"
No Load Speed	30,000 RPM
Battery	18v LXT® Lithium-Ion 4.0 Ah
Overall Length	12-3/8"
Net Weight (w/battery)	3.7 lbs.
Shipping Weight	11 lbs.



2,500RPM

FS2500



2,500 RPM DRYWALL SCREWDRIVER

Precision Balance with Less Weight

- Powerful 6.0 AMP motor with 0-2,500 RPM to handle the most challenging applications
- Less weight (only 3.4 lbs.) with precision balance for ultimate user comfort
- Built-in LED light illuminates the work area for greater productivity in low-light applications
- Steel-reinforced belt clip for user convenience and increased durability

Model FS2500 Includes: 5/16" Magnetic Nutsetter, 2-5/8" (784804-5)

Bit Type	1/4" Hex
No Load Speed	0 - 2,500 RPM
AMPS	6
Overall Length	11"
Net Weight	3.4 lbs.
Shipping Weight	6 lbs.

UNPLUG THE CORD

4.0Ah BATTERY

PUSH(DRIVE)



In lock-on mode, the motor starts only when the fastener is engaged to save battery power and reduce noise

WORK ALL DAY



Model XSF03M Includes: 2 ea. 4.0 Ah Battery (BL1840), Rapid Optimum Charger (DC18RC), Tool Case
Model XSF03Z Includes: Tool only - battery and charger not included

Hex Shank	1/4"
No Load Speed	0 - 4,000 RPM
Battery	18v LXT® Lithium-Ion 4.0 Ah
Overall Length	9-7/8"
Net Weight (w/battery)	3.8 lbs.
Shipping Weight	12.4 lbs.

* 4.0 Ah battery will hang up to 40 sheets of 4x8' 1/2" Drywall, 1-1/4" (32mm) screw into .59" (15mm) drywall into 20 gauge (1.0mm) steel stud using Push Drive™
** 1-1/4" (32mm) screw, .59" (15mm) drywall into 20 gauge (1.0mm) steel stud