

## **P3 Comforts One-piece toilet Duravit Rimless for SensoWash**® # 217551..01 / 217551..85



| One-piece toilet Duravit Rimless for SensoWash®   | Dimension    | Weight         | Order number |
|---|--------------|----------------|--------------|
| US-version, connecting elements for SensoWash with concealed<br>connections included, elongated with syphonic jet action, 305<br>mm/12" rough-in, only in combination with SensoWash, vertical<br>outlet  |              |                |              |
| Colors  |              |                |              |
| 00 White Alpin 20 HygieneGlaze (an antibacterial ceramic glaze that provides almost indefinite effectiveness)   |              |                |              |
| Variant   |              |                |              |
| ♦ 1,32/0,92 gpf (5/3,5 lpf), with Dual Flush mechanism  | 380 x 710 mm |                | 21755101     |
| ♦ 1,28 gpf (4,8 lpf), with Single Flush piston valve, top flush   | 380 x 710 mm |                | 21755185     |
| Accessory   |              |                |              |
| Mounting set for One-piece and Two-piece toilets, 1/2", ASIA-<br>version  |              | 0.480 kilogram | 001416       |
| Mounting set for One-piece and Two-piece toilets, Outflow 3/8"<br>- external thread, Wall Connection 1/2" - internal thread, 1/2",<br>US-version  |              | 0.480 kilogram | 001417       |
| Suitable products   |              |                |              |
| SensoWash® Slim shower toilet seat for P3 Comforts* with<br>concealed connections, Remote control included, Locking<br>function via remote control, Rear-, Lady- and Comfortwash,<br>Individual adjustment of water temperature as well as spray<br>wand position and water spray intensity, Self-cleaning spray<br>wand, with soft closure, Night light, Seat and lid easy removable<br>one-handed, Automatic drainage in periods of prologed disuse,<br>on / off-button, 386 x 540 mm | 386 x 540 mm |                | 611400       |

All drawings contain the necessary measurements which are subject to standard tolerances. They are stated in mm and are non-binding. Exact measurements, in particular for customised installation scenarios, can only be taken from the finished ceramic piece.