

## CAPACITY



Miters 0-47° left and 0-57° right;  
bevels 0-45° left and 0-5° right

## TECHNOLOGY

**AUTOMATIC  
SPEED CHANGE™**  
ADJUSTS SPEED & TORQUE FOR OPTIMUM PERFORMANCE

Automatic Speed Change™ adjusts cutting speed and torque during cut for optimum performance

## PERFORMANCE

Two 18v LXT® Batteries deliver the power and performance of a corded miter saw

## PORTABLE &amp; POWERFUL



**NEW XSL02Z**

### 18v X2 LXT® BRUSHLESS 7-1/2" COMPOUND MITER SAW

Powerful BL™ Brushless Motor Delivers 5,700 RPM for Faster Cutting

- Two 18v LXT® Lithium-Ion Batteries deliver the power and performance of a corded miter saw without leaving the 18v LXT® platform
- Automatic Speed Change™ technology adjusts cutting speed and torque during cut for optimum performance
- The BL™ Brushless Motor eliminates carbon brushes, enabling the BL Motor to run cooler and more efficiently for longer life
- Efficient BL™ Brushless motor is electronically controlled to optimize battery energy use for up to 50% longer run time per charge

Model XSL02Z Includes: 7-1/2" 40T C.T. Miter Saw Blade (A-90629); Battery and Charger not included

Tool only - battery and charger not included

Blade Diameter	7-1/2"
Arbor	5/8"
Max. Cutting Capacity (Bevel/Miter): 90°/90° (2-1/16" x 11-3/4"), 45°/45° (2-1/16" x 8-3/8")	
No Load Speed	5,700 RPM
Battery	2X 18v LXT® Lithium-Ion
Dimensions (LxWxH)	25-3/4" x 17" x 17-1/2"
Net Weight (with battery)	28.9 lbs.
Shipping Weight	38 lbs.



**XSL01**

### 18v LXT® 7-1/2" COMPOUND MITER SAW KIT

Large Cutting Capacity up to 2-1/16" and 11-3/4" Crosscuts at 90°

- Powerful Makita-built motor delivers 2,200 RPM
- Weights only 27.5 lbs. with battery for reduced operator fatigue
- Four steel rail sliding system increases rigidity to produce superior accurate cuts
- Miters 0-47° left and 0-57° right; bevels 0-45° left and 0-5° right

Model XSL01 Includes: (2) 18v LXT® Lithium-Ion 3.0Ah Battery (BL1830), 18v Lithium-Ion Rapid Optimum Charger (DC18RC), 7-1/2" 40T C.T. Miter Saw Blade (A-90912), (2) Extension Wing (322312-4), Vertical Vise (122571-8), Dust Bag (122852-0), Triangular Rule (762001-3), Socket Wrench (782223-9)

Model XSL01Z Includes: Tool Only; Battery and Charger not included

Blade Diameter	7-1/2"
Arbor	5/8"
Max. Cutting Capacity (Bevel/Miter): 90°/90° (2-9/16" x 11-3/4"), 45°/45° (1" x 11-3/4")	
No Load Speed	2,200 RPM
Battery	18v LXT® Lithium-Ion
Dimensions (LxWxH)	25-3/4" x 17" x 17-7/8"
Net Weight (with battery)	27.5 lbs.
Shipping Weight	44 lbs.



**XMT03Z**

**XMT035**

### 18v LXT® MULTI-TOOL KIT

"Tool-less" Clamp System for Fast Accessory Installation

- 18v LXT® Lithium-Ion battery provides up to 20 minutes of continuous run time
- Variable speed control dial (6,000-20,000 OPM) enables user to match the speed to the application
- 3.2° oscillation angle engineered for faster, more aggressive cutting and sanding
- Large on/off slide switch with lock-on button for operator convenience

Model XMT035 Includes: (2) 18v LXT® Lithium-Ion 3.0Ah Battery (BL1830), 18v Lithium-Ion Rapid Optimum Charger (DC18RC), 1-1/4" Plunge Blade (BIM) (A-95255), Multi-Tool Adapter (313249-6), Multi-Tool Adapter (313248-8), Tool Bag

Model XMT03Z Includes: Tool Only; Battery and Charger not included

Oscillations Per Minute	6,000 - 20,000 OPM
Oscillation Angle	3.2°
Battery	18v LXT® Lithium-Ion
Overall Length	13-3/8"
Net Weight (with battery)	4.9 lbs.
Shipping Weight	14.1 lbs.



**XOB01Z**

**XOB01**

### 18v LXT® 5" RANDOM ORBIT SANDER KIT

Corded Performance without the Cord

- Three speed settings (7,000/9,500/11,000 OPM) engineered for fast material removal
- Up to 40 minutes (low speed) and 20 minutes (high speed) of run time on a single charge
- Large 1/8" random orbit action engineered for fast sanding and swirl-free finish
- One-touch electronic speed control switch provides fast, medium and low settings
- Ergonomically designed body and grip for increased operator comfort

Model XOB01 Includes: (2) 18v LXT® Lithium-Ion 3.0Ah Battery (BL1830), 18v Lithium-Ion Rapid Optimum Charger (DC18RC), Tool Bag

Model XOB01Z Includes: Tool Only; Battery and Charger not included

Pad Size (round)	4-7/8"
Abrasive Disc Size	5"
Orbits Per Minute (3 speed)	7,000, 9,500, 11,000 OPM
Orbit Diameter	1/8"
Battery	18v LXT® Lithium-Ion
Overall Length	6-7/8"
Net Weight (with battery)	3.6 lbs.
Shipping Weight	12 lbs.



**XPK01Z**

**XPK01**

### 18v LXT® 3-1/4" PLANER KIT

Planes Up to 3-1/4" Wide and 5/64" Deep in a Single Pass

- 2-blade cutter head with double edge carbide blades for added performance and smooth finish
- High power-to-weight ratio; weighs only 7.4 lbs.
- 14,000 RPM motor engineered for fast stock removal
- Click depth adjustment knob with easy-to-read scale with settings from 0" to 5/64"
- Spring-loaded stand elevates the base to protect the blades and workpiece

Model XPK01 Includes: (2) 18v LXT® Lithium-Ion 3.0Ah Battery (BL1830), 18v Lithium-Ion Rapid Optimum Charger (DC18RC), 3-1/4" Planer Blade Set (D-46246), Blade Gauge (123062-2), Socket Wrench (782209-3), Tool Bag

Model XPK01Z Includes: Tool Only; Battery and Charger not included

Planing Width	3-1/4"
Planing Depth	5/64"
No Load Speed	14,000 RPM
Battery	18v LXT® Lithium-Ion
Overall Length	13-1/8"
Net Weight (with battery)	7.4 lbs.
Shipping Weight	16.3 lbs.



**XJP03Z**

### 18v LXT® PLATE JOINER

Delivers up to 300 Cuts for #0 Biscuits on a Single Charge

- Rack-and-pinion vertical fence system engineered for accurate fence adjustments
- Cast aluminum pivot fence with three positive stops at 0°, 45° and 90°, and easy centering on 3/4" material
- Six depth settings with one-touch stops for #0, #10, and #20 and most common biscuits sizes
- Cordless plate joiner provides portability and performance in the field or in the shop without the cord
- Large and easy-to-operate cam locks for fence adjustments

Model XJP03Z Includes: Tool Only; Battery and Charger not included

Blade Diameter	4"
Cutting Capacity (depth)	3/4"
No Load Speed	6,500 RPM
Battery	18v LXT® Lithium-Ion
Overall Length	13-3/4"
Net Weight (with battery)	6.7 lbs.
Shipping Weight	8.2 lbs.