







Modern Recessed

<u>SPECIFICATIONS - MicroTouch Control</u>

Construction	6061 Billet Aluminum
Display	16 LED Temperature Display
Interface	3 Capacitive Touch Buttons
Communication	ThermaSol CAN Bus
Supply Voltage	5V DC

SPECIFICATIONS (cont.) - Aromatherapy Steam Head

Construction	. 360 Half Hard Brass
Aromatherapy	Integral Reservoir
OperationThermal operat	ed retractable outlet

Basic Functions:

- · Recall last steam settings
- · Turn steam system on or off
- Set desired steam shower temperature
- Operate PowerFlush™ cleaning system
- Diagnostic LEDs, display troubleshooting errors codes
- Patent Pending Infrared temperature sensing
- Smooth operation with capacitive touch technology (CTT)

Aromatherapy Retractable Steam Head:

- Patented NoTouch™ retractable steam head with integral Aromatherapy well
- Available in 14 finishes
- Sleek new design dispenses steam safely
- Whisper quiet operation

Installation Notes:

The control should be installed 60" inches from the floor of the shower, inside the shower only, and away from the steam head.

The steam head should be installed 12" inches from the floor and 6" from any wall. Locate as far as possible from the bathing seating area or location of the users and not below any fixtures.

Finish Chart:

Select desired finish and replace XX with code. No-Touch Aromatherapy steam head and control finishes.

PC = Polished Chrome

SC = Satin Chrome

PB = Polished Brass

SB = Satin Brass

AB = Antique Brass

COP = Polished Copper

ACOP = Antique Copper

PN = Polished Nickel

SN = Satin Nickel BN = Black Nickel

AN = Antique Nickel
PG = Polished Gold

ORB = Oil Rubbed Bronze

WHT = White

Product Specification:

The user interface control shall be 3.75" x 3.75" x 0.63" in dimension. The Control shall be made from billet aluminum and includes the ability to operate and control: Smart Steam and PowerFlush™ System, using 100% networked digital technology.

Shipping Information:

Weight	4 lbs.
Length	12 in.
Width	12 in.
Height	6 in.

Style Information: The control is Modern Recessed and the steam head is Modern

Modern recessed is flush with wall within: .10"

For any further assistance please contact
ThermaSol at 800.776.0711 or
sales@thermasol.com



