

SNAP-ACTION CAST IRON SUMP/EFFLUENT PUMPS

APPLICATIONS

Ideal for average- to high-volume water and effluent removal in residential spaces such as basements, laundry facilities, and crawl spaces.

FEATURES & BENEFITS

- Automatic submersible cast iron sump/effluent pump
- 1-1/2" FNPT discharge
- Integrated snap-action float switch suitable for use in narrow basins (11" or greater)
- · Solid float will never become waterlogged
- Built-in rod protection prevents float from contacting basin
- Clog-resistant design (1/2" diameter semi-solids handling)
- 10' cord





Model	Item No.	UPC	НР	Volts	Amne	Discharge	Cord Lenath						Shut-	On/Off	Basin
Model	iteili No.	UPC	пР	VOILS	Allips	Discharge	Length	5′	10′	15′	20′	30'	Off	Levels	Diameter
RL-33SC	14942652	0 10121 14579 5	1/3	115	5	1-1/2" FNPT	10'	3200	3000	2500	2200	-	28′	On: 8"-11" Off: 2"-5"	11" or more
RL-50SC	14942653	0 10121 14580 1	1/2	115	6.5	1-1/2" FNPT	10'	4000	3420	3090	2800	1680	36′	On: 8"-11" Off: 2"-5"	11" or more

CARTON SPECIFICATIONS

Model	Length	ength Width Heigh		Weight Carton (lbs) Cubes (cu ft)		Pallet Quantity	Quantity per Layer	Layers per Pallet
RL-33SC	9.75"	11"	12.75"	27.75	0.79	48	16	3
RL-50SC	10.25"	11.50"	13.75"	28.46	0.94	36	12	3

Snap-Action Sump/Effluent Pumps

