## **High-Leverage Diagonal-Cutting Pliers**

Rivet is closer to cutting edge

cutting and gripping power than other pliers designs

## FORGED STEEL

from Klein's US-made proprietary blend



Hot-riveted joint ensures smooth action

and no handle wobble

**Induction hardened** cutting knives for long life

Short jaws and beveled cutting edges permit close cutting of wire

## **High-Leverage Diagonal-Cutting Pliers**

Includes core High-Leverage Diagonal-Cutting features plus:

- Glow-in-the-Dark grips are easily spotted in dark or low lit areas (Cat. Nos. D2000-28GLW)
- Cat. No. D243-8 cleanly strips 12-14 AWG wire







SPLIT TETHER RING D228-8TT



12-14 AWG SOLID WIRE STRIPPING HEAD D243-8



PLASTIC-DIPPED GLOW-IN-THE-DARK



JOURNEYMAN™ Plastic-Dipped **Dual-Material** 



INS INSULATED 2-Layer Protection



EINS INSULATED 3-Layer Protection

**∤** 1000 V

**№ 1000 V** 

| Cat. No.  | Jaw Length       | Jaw Width       | Jaw Thickness   | Cutting Knives | Handle Color     | Handle Finish             | Overall Length   |  |  |  |  |
|---|------------------|-----------------|-----------------|----------------|------------------|---------------------------|------------------|--|--|--|--|
| D228-7  | 0.779" (1.98 cm) | 1.25" (3.18 cm) | 0.46" (1.17 cm) | Standard       | Red              | Plastic-Dipped            | 7" (17.78 cm)    |  |  |  |  |
| D228-8  | 0.781" (1.98 cm) | 1.25" (3.18 cm) | 0.46" (1.17 cm) | Standard       | Red              | Plastic-Dipped            | 7.98" (20.27 cm) |  |  |  |  |
| D228-8-INS  | 0.813" (1.98 cm) | 1.25" (3.18 cm) | 0.46" (1.17 cm) | Standard       | Orange           | 2-Layer Insulation        | 8.24" (20.93 cm) |  |  |  |  |
| D228-8TT  | 0.813" (1.98 cm) | 1.25" (3.18 cm) | 0.46" (1.17 cm) | Standard       | Red              | Plastic-Dipped            | 8.24" (20.93 cm) |  |  |  |  |
| J228-8  | 0.813" (1.98 cm) | 1.25" (3.18 cm) | 0.46" (1.17 cm) | Standard       | Red/Black        | Journeyman™ Dual-Material | 8.08" (20.52 cm) |  |  |  |  |
| D243-8  | 0.813" (1.98 cm) | 1.25" (3.18 cm) | 0.46" (1.17 cm) | Standard       | Red              | Plastic-Dipped            | 7.98" (20.27 cm) |  |  |  |  |
| With heavy-duty cutting knives designed to cut ACSR, screws, nails and most hardened wire |                  |                 |                 |                |                  |                           |                  |  |  |  |  |
| 200028EINS  | 0.83" (2.11 cm)  | 1.25" (3.18 cm) | 0.49" (1.24 cm) | Standard       | Orange/Gray      | 3-Layer Insulation        | 8.15" (20.70 cm) |  |  |  |  |
| D2000-28  | 0.83" (2.11 cm)  | 1.25" (3.18 cm) | 0.49" (1.24 cm) | Standard       | Light Blue       | Plastic Dipped            | 7.98" (20.27 cm) |  |  |  |  |
| D2000-28-INS  | 0.83" (2.11 cm)  | 1.25" (3.18 cm) | 0.49" (1.24 cm) | Standard       | Orange           | 2-Layer Insulation        | 8.24" (20.93 cm) |  |  |  |  |
| D200028GLW  | 0.83" (2.11 cm)  | 1.25" (3.18 cm) | 0.49" (1.24 cm) | Standard       | Glow-in-the-Dark | Plastic-Dipped            | 7.98" (20.27 cm) |  |  |  |  |
| J2000-28  | 0.83" (2.11 cm)  | 1.25" (3.18 cm) | 0.49" (1.24 cm) | Standard       | Light Blue/Black | Journeyman™ Dual-Material | 8" (20.32 cm)    |  |  |  |  |

## **Diagonal-Cutting Pliers with Stripping Holes**

Includes core High-Leverage Diagonal-Cutting features plus:

Cleanly strips 12-14 AWG solid wire



D243-8

| Cat. No. | Jaw Length       | Jaw Width       | Jaw Thickness   | Cutting Knives | Handle Color | Handle Finish  | Overall Length   |
|----------|------------------|-----------------|-----------------|----------------|--------------|----------------|------------------|
| D243-8   | 0.781" (1.98 cm) | 1.25" (3.18 cm) | 0.46" (1.17 cm) | Standard       | Red          | Plastic-Dipped | 7.98" (20.27 cm) |