PEERLESS

_ 7" (178 mm)

8" (203 mm)

18"(457 mm)

min.

max.

Face of plasterguard

should be flush with-

2"

(51 mm)


finish wall line

P188710 P188720

C/L Supply

lines

Supply



TUB AND SHOWER FAUCET

Shower Only (PTT188710 Series)
 Tub/Shower (PTT188720 Series)

STANDARD SPECIFICATIONS:

- Slip-on tub spout, model PTT18820.
- Pressure balanced bath mixing valve.
- Tub/Shower. Requires 1 1/2" wall cavity.
- Back-to-back installation capability.
- Temperature control to rotate a maximum of 120° from full cold to the maximum temperature.
- Temperature only controlled with handle.
- Shower head maximum flow rate is 1.75 gpm @ 80 psi,
 6.6 L/min @ 550 kPa.

WARRANTY:


 Parts and Finish - Lifetime limited warranty; or for commercial purchasers, 10 years for multi-family residential (apartments and condominiums) and 5 years for all other commercial uses, in each case from the date of purchase.




COMPLIES WITH


- ASME A112.18.1 / CSA B125.1
- EPA WaterSense[®]

Indicates compliance to ICC/ANSI A117.1 - Valve control only



Praramon





2 1/2"

(64 mm)