



FLOOR SCRAPER



FLOOR SCRAPER

Style	Size	Part No.
SLEDGE™ SDS Max Floor Scraper	6" x 6" x 25"	48-62-4096
Spline / Round Hex 2-Piece Floor Scraper	6" x 25"	48-62-2016
Floor Scraper Replacement Blade	1.5 mm	48-62-1906
Floor Scraper Replacement Fastener Kit	-	48-62-1911
Floor Scraper Replacement Hold Down Plate	-	48-62-1901
Floor Scraper Replacement Mount Head (Yoke)	-	48-62-1921
Floor Scraper Replacement Shank	15-1/2"	48-62-1916

SDS MAX CHISELS



SDS MAX CHISELS

Tip Type	Style	Application	Size	1 Pack	Bulk
	Bull Point	Starts a hole in concrete slabs, general chipping and breaking	12"	48-62-4075	48-62-4175 (25 pk)
	Bull Point		18"	48-62-4077	48-62-4177 (25 pk)
	Bull Point		24"	48-62-4062	-
	Flat Chisel	General chipping and breaking	1" x 12"	48-62-4079	48-62-4179 (25 pk)
	Flat Chisel		1" x 18"	48-62-4081	48-62-4181 (25 pk)
	Flat Chisel		1" x 24"	48-62-4064	-
	Scaling Chisel	Cleans concrete, scale, rust, cuts troughs and some asphalt	1-1/2" x 12"	48-62-4082	-
	Scaling Chisel		2" x 12"	48-62-4085	48-62-4185 (25 pk)
	Scaling Chisel		4-1/2" x 14"	48-62-4086	-
	Tile Chisel	Removes tiles, laminates and other composite materials, removes concrete spillage	3-1/4" x 12"	48-62-4088	-
	Brick Channel Chisel	Creates a channel to run conduit in block wall, wings aid in depth control	1-1/4" x 12"	48-62-4097	-
	Concrete Channel Chisel	Creates a channel to run conduit in concrete	1" x 12"	48-62-4098	-

SDS MAX CHISELS

Tip Type	Style	Application	Size	1 Pack	Bulk
	Seam Tool	Removes mortar between brick or block, cuts narrow channels	1-1/8" x 12"	48-62-4080	-
	Bushing Tool	Removes excess concrete, produces exterior finish, roughens surface before surface coating	1-3/4" x 9-1/4"	48-62-4065	-
	Carbide Tipped Bushing Tool	Carbide provides longer life, removes excess concrete, produces exterior finish, roughens surface before surface coating	1-1/2" x 10"	48-62-4063	-
	Carbide Slotting Tool	Carbide teeth provide longer life, creates large openings in concrete in between holes	1-1/2" x 11"	48-62-4074	-
	Asphalt Cutter	Cuts asphalt or hard ground (DO NOT use for concrete)	5" x 16-1/2"	48-62-4066	-
	Clay Spade	Digs up clay, hard packed gravel and dirt	4-1/2" x 16-5/8"	48-62-4094	48-62-4194 (12 pk)
	Ground Rod Driver	Drives soft ground rods	10" L - 1/2" and 5/8" Rod Dia.	48-62-4093 NEW	-
	Ground Rod Driver	Drives soft ground rods	10-1/2" L - 5/8" and 3/4" Rod Dia.	48-62-4091	-
	Tamper Shank	Used to mount tamper plate	12"	48-62-4092	-
	Tamper Plate	Compacts dirt, tamps asphalt	5" x 5"	48-62-3060	-

SDS MAX ONE-PIECE CORE BITS

OVERVIEW

MILWAUKEE's SDS Max One-Piece Carbide Tipped Core Bits are ideal for drilling large holes where the depth is relatively shallow. The core bit cuts a kerf only. The inside core must be removed by the operator before deeper drilling can be accomplished. Includes Centering Bit 48-20-5495. Use Drift Key 48-20-5497 (not included) to remove Centering Bit from the one-piece core bit. The one-piece core bits are available in SDS Max or Spline shanks. They come in a variety of diameters ranging from 1-1/2" to 6" with overall lengths of 11-3/8" or 22" and a drilling depth of 3". The asymmetric tooth pitch with alternating tooth geometries creates faster material pulverization. The one-piece design maximizes energy transfer and the thick wall core body is durable even in large hammers. The fluted core exterior minimizes friction loss and removes debris faster.

FEATURES

- Asymmetrical and Alternating Teeth: Faster material pulverization
- Thick Wall Core Body: Durability even in large hammers
- Includes Centering Bit: Reduce bit walking and create exact spot drilling

