

THE SMALLEST, MOST INTELLIGENT PRESS TOOL

M18™ FORCE LOGIC™
Long Throw Press Tool Kit
2773-22L



ADJUST

Adjustable stroke for optimized cycle time

ACCESS

Lightest, in-line design for unrivaled access

PRESS

Longest calibration interval, 50,000 cycles



SPECIFICATIONS	
DESCRIPTION	SPECIFICATIONS
Force	7,200 lbs
Pipe Capacity	1/4" – 4" (Varies by Material)
Approx. Cycle Time	4 Second Stroke (8 Second Extended Stroke)
Calibration Interval	50,000 Cycles
Length (without battery & jaw)	18.3"
Weight (without battery & jaw)	7.3 lbs

KITS

M18™ FORCE LOGIC™
Long Throw Press Tool
Kit w/ 1/2" - 1" SS Jaws
2773-22L

Includes: 2773-20L Long Throw Press Tool, (2) M18™ REDLITHIUM™ XC3.0 Battery Packs, 1/2", 3/4", 1" IPS-IA Jaws, Multi-Voltage Charger and Carrying Case.



M18™ FORCE LOGIC™
Long Throw Press
Tool Kit
2773-20L

Includes: 2773-20L Long Throw Press Tool, (2) M18™ REDLITHIUM™ XC3.0 Battery Packs, Multi-Voltage Charger and Carrying Case.
Jaws Not Included.



CTS



IPS



PEX



ACR



REQUIRES RING JAWS



COMPATIBILITY

FITTING MFR	Viega®					Apollo Valves / Elkhart		
FITTING SYSTEM	ProPress® up to 4"	ProPress® G up to 2"	MegaPress® up to 4"	MegaPress® G up to 4"	PureFlow® PEX Press up to 2"	ApolloPress® up to 4"	PowerPress up to 2"	
FITTING MFR	Mueller Industries			NIBCO®	Anvil®	Isotubi USA	Wolverine Brass®	Standard PEX Fittings
FITTING SYSTEM	Streamline PRS™ up to 4"	Streamline® STL & STL-G up to 2"	Streamline® ACR up to 1-1/8"	Copper Fittings up to 2"	BenchPress™ up to 2"	AnvilPress™ up to 2"	Isotubi Stainless Steel up to 1-1/4"	Up to 2"
							ASTM F1807 & F2159 PEX Crimp up to 2"	Up to 1-1/8"

MATERIAL ICON KEY



For most up to date fitting compatibility information, visit milwaukeeetool.com

THE SMALLEST, MOST INTELLIGENT PRESS TOOL

M18™ FORCE LOGIC™
Press Tool Kit w/ ONE-KEY™
2922-22



ACCESS

Lightest, in-line design for unrivaled access

ALIGN

Easy open jaw for one-handed use

PRESS

Auto-cycle ensures full press every time

REPORT

Sync Wirelessly

Report Performance

See page 14 for more ONE-KEY™ information



KITS

M18™ FORCE LOGIC™
Press Tool Kit
w/ ONE-KEY™ with
1/2" - 2" CTS Jaws
2922-22

Includes: 2922-20 Press Tool w/ ONE-KEY™,
(2) M18™ REDLITHIUM™ CP2.0 Battery Packs,
1/2", 3/4", 1", 1-1/4", 1-1/2", 2" CTS Jaws,
Multi-Voltage Charger and Carrying Case.



M18™ FORCE LOGIC™
Press Tool Kit
w/ ONE-KEY™
2922-22M

Includes: 2922-20 Press Tool w/ ONE-KEY™,
(2) M18™ REDLITHIUM™ CP2.0 Battery Packs,
1/4", 3/8", 1/2", 5/8", 7/8" Streamline® ACR Jaws,
Multi-Voltage Charger and Carrying Case.



Also available:

M18™ FORCE LOGIC™ Press Tool Kit
w/ ONE-KEY™ (2922-20)
Jaws Not Included.



CTS

1/2" CTS-V
49-16-2650

3/4" CTS-V
49-16-2651

1" CTS-V
49-16-2652

1-1/4" CTS-V
49-16-2653

1-1/2" CTS-V
49-16-2654

2" CTS-V
49-16-2655

2-1/2" CTS-Vr1
49-16-2656

3" CTS-Vr1
49-16-2657

4" CTS-Vr1
49-16-2658

2-1/2" - 4" CTS-Vr1
49-16-2690

IPS

1/2" IPS-P
49-16-2650B

3/4" IPS-P
49-16-2651B

1" IPS-P
49-16-2652B

1-1/4" IPS-Pr1
49-16-2653B

1-1/2" IPS-Pr1
49-16-2654B

2" IPS-Pr1
49-16-2655B

1/2" - 1" IPS-P
49-16-2696

1/2" - 2" IPS-Pr1
49-16-2697

1/2" IPS-IA
49-16-2650S

3/4" IPS-IA
49-16-2651S

1" IPS-IA
49-16-2652S

1-1/4" IPS-IAr1
49-16-2653S

REQUIRES
RING JAWS

* r1 Ring Jaw
49-16-2659

PEX

1/2" 49-16-2651C

3/4" 49-16-2653C

1" 49-16-2654C

1-1/4" 49-16-2655C

1-1/2" 49-16-2656C

2" 49-16-2657C

ACR

1/4" Streamline® ACR
49-16-2650M

3/8" Streamline® ACR
49-16-2652M

1/2" Streamline® ACR
49-16-2653M

5/8" Streamline® ACR
49-16-2654M

3/4" Streamline® ACR
49-16-2655M

7/8" Streamline® ACR
49-16-2656M

1-1/8" Streamline® ACR
49-16-2657M

1/4" - 7/8" Streamline® ACR
49-16-2661M

1/4" RLS® ACR
49-16-2650R

3/8" RLS® ACR
49-16-2652R

1/2" RLS® ACR
49-16-2653R

5/8" RLS® ACR
49-16-2654R

3/4" RLS® ACR
49-16-2655R

7/8" RLS® ACR
49-16-2656R

1-1/8" RLS® ACR
49-16-2657R

1/4" - 1-1/8" RLS® ACR
49-16-2662R

COMPATIBILITY

FITTING MFR	Viega®					Apollo Valves / Elkhart		
FITTING SYSTEM	ProPress® up to 4"	ProPress® G up to 2"	MegaPress® up to 2"	MegaPress® G up to 2"	PureFlow® PEX Press up to 2"	ApolloPress® up to 4"	PowerPress up to 2"	
FITTING MFR	Mueller Industries			NIBCO®	Anvil®	Isotubi USA	Wolverine Brass®	Standard PEX Fittings
FITTING SYSTEM	Streamline PRS™ up to 4"	Streamline® STL & STL-G up to 2"	Streamline® ACR up to 1-1/8"	Copper Fittings up to 2"	BenchPress™ up to 2"	AnvilPress™ up to 2"	Isotubi Stainless Steel up to 1-1/4"	Up to 2"
								ASTM F1807 & F2159 PEX Crimp up to 2"
								Up to 1-1/8"

MATERIAL ICON KEY

COPPER

STAINLESS STEEL

BLACK PIPE

PEX

ACR COPPER

For most up to date fitting compatibility information, visit milwaukeetool.com