

About Us

Redback focuses on the development of innovative lawn & garden products. Since its start in 2000, Redback has grown to over 400 committed employees and exports to more than 30 countries.

Quality is our focus. Our battery powered garden tools use the highest grade materials while maintaining a sleek design. All of our products are backed by a *2-year warranty.

We work closely with our partners to provide excellent customer service and to continue to develop new products

*must register your product at redbacktools.com



Table Of Contents

- 3 MowRo
- 7 Redback Power
- 9 String Trimmers
- 13 Chainsaws
- 17 Blowers
- 21 Hedge Trimmers
- 25 Lawn Mowers
- 27 Augers
- 30 Batteries & Chargers

ACLIRO

The Lawn Mower Robot



Safe & Environmentally Friendly

MowRo was designed with safety in mind. Don't be 1 of the 37,000 Americans that get injured by a push mower this year. Keep yourself and your loved ones safe with MowRo.

With MowRo you will reduce your water usage, fertilization, waste materials, pollution, and hours of mowing. Help create a more sustainable future with MowRo.



Child & Pet Proof

> **Protective Blade Guard**







No Fuel Costs or Spills

No Harmful Greenhouse Gases

Exhaust Fumes



Easy Installation With **MCURO**



Select a location within 20ft of an outlet that has adequate room for MowRo to enter and exit.



Install boundary wire flush with the ground, remembering to stay 12" away from walls and 4" away from flat surfaces.



Set your security pin code, the size of your lawn, and the time of day you want MowRo to cut your yard.





Automated Mow Scheduling



Returns To Dock When The Battery is Low



Climbs Slopes Up To 30°



Ultra Quiet Silent Motor



Senses Rain, Disengages Blades & Returns To Docking Station



Changes Course To Avoid Foreign Objects



Controlled Via Radio Wave Perimeter Wire



Adjustable Steel Blades



MowRo Specifications	RM-24	RM24-SMRT
App Enabled	No	Yes
Battery-Voltage/Capacity	28V-4Ah	28V-4Ah
Charger Current (A)	1.8	1.8
Average Charging Time (Hrs)	3	3
Cutting Motor	Brushless	Brushless
Driving Motor	Brushless	Brushless
Working Time (min)	90	90
Blade Speed (rpm)	2900	2900
Cutting Width (in)	9.5"	9.5"
Cutting Height (in)	1.0"-2.5"	1.0"-2.5"
Max. Working Area (acre)	0.25	0.25
Slope (Max °)	30°	30°
MAX driving speed (ft/s)	1.5	1.5
Noise (dBA)	65	65
Package Size (in)	31 x 22 x 13	31 x 22 x 13
Net Weight (lbs)	34	34



SWIFT SERIES

VALUE-DRIVEN

Every tool comes with a battery & charger in the Swift Series. This series is ideal for quick jobs around smaller yards.



FLEX SERIES

CUSTOMIZABLE

The Flex series offers our widest range of tools, batteries, and chargers. This series is ideal for frequent use around mid-size to larger yards.





PRO SERIES

POWERFUL

Bringing professional power to battery operated tools, this series is ideal for a wide variety of jobs and property sizes.











EB310D



The 40V EB310D features 3 small blades instead of standard string which makes upkeep and maintenance a breeze.

E312D



The easy to use 40V E312D has a comfort handle grip and bump feed spool.

EA316



The 120V EA316 is light weight and gets more done with its wide 16" cutting width.



String Trimmer Specifications	SWIFT SERIES EB310D	FLEX SERIES E312D	PRO SERIES EA316
Voltage (V)	40	40	120
Cutting Diameter (in)	9.8"	12"	16"
Motor Power	Brushed	Brushed	Brushless
No Load Speed (rpm)	9000	7500	7500
Net Weight (lbs)	4.7	6.8	6.8
Sound Power Level (dBA)	96	96	96
Handle Type	Loop	Loop	Loop
Rotating Handle (°)	90° to left	90° to left	90° to left
Adjustable Head (°)	0-72°	0-72°	0-72°
Pole Diameter (in)	1"	1"	1"
Cutting Tool	Plastic Blades	Nylon Line	Nylon Line
Running Time 2.0 AH (no load) (min)	80	27	49
Running Time 3.0 AH (no load) (min)	-	-	76
Running Time 4.0 AH (no load) (min)	-	51	-
Running Time 6.0 AH (no load) (min)	-	80	-







	SWIFT SERIES		FLEX SERIES	PRO SERIES
Chainsaw Specifications	EB212D	EB608D	E212C	EA218
Voltage	40	40	40	120
Chain Speed (ft/s)	33	19.5	33	33
Saw Guide Bar Length (in.)	12"	7.9"	12"	18"
Oil Capacity (ml)	150	70	160	160
Motor Power	Brushed	Brushed	Brushless	Brushless
Net Weight (lbs)	6.6	6.6	11	12.56
Sound Power Level (dBA)	106	96	103	103
Max Branch Thickness (in.)	12"	7.5"	12"	18"
Extension Range of Shaft (in.)	-	0"-15.75"	-	-
Running Time 2.0 AH (no load) (min)	30	35	25	64
Running Time 3.0 AH (no load) (min)	-	-	-	105
Running Time 4.0 AH (no load) (min)	-	-	50	-
Running Time 6.0 AH (no load) (min)	-	-	76	-

EB212D



EB608D





The 40V EB212D is perfect for quick jobs. It features a 12" cutting blade and is very light weight.

Take your outdoor work to new heights with the Swift Pole saw that extends your reach over 6ft.

E212C



EA218







The 40V E212C has a brushless motor and 12" cutting blade. Perfect for any job around the house.

The EA218's 120V power and 16" blade helps tackle larger limbs, and is powerful enough to handle all of your projects.







EB430D





The 40V EB430D blower packs a punch when cleaning debris and is very quiet.

E435C





The 40V E435C allows you to select the velocity that works best for your project. Start it's brushless motor with the push of a button.

EA460





You'll be blown away by the 120V EA460. It's brushless motor and longer run times will keep you going during any project.

EBV480D



EV480D







The 40V EBV480D is a versatile blower/vacuum/mulcher that can helps eliminate bagging/waste by mulching leaves as they are vacuumed.

The 40V EV480D offers you multiple battery options allowing you to select the run times for your specific needs. Enjoy blowing, vacuuming, and mulching with the same tool.

Leaf Blower Specifications	SWIFT	SERIES	FLEX SERIES		PRO SERIES
Leaf Blower Specifications	EB4300D	EV480D	E435C	EBV480D	EA460
Voltage	40	40	40	40	120
Air Volume (blower) (cfm)	247	155	385	155	514
Air Volume (vacuum) (cfm)	-	346	-	346	-
Air Speed (blower) (mph)	87	116	121	116	122
Air Speed (vacuum) (mph)	-	102	ı	102	-
Motor Power	Brushed	Brushed	Brushless	Brushed	Brushless
Net Weight (lbs)	4.2	9.9	5.5	9.9	5.95
Sound Power Level (dBA)	93.8	110	110	110	102
No Load Speed (rpm)	0-25,000	0-25,000	0-25,000	0-25,000	0-25,000
Mulching Ratio	-	30:1	ı	30:1	-
Running Time 2.0 AH (no load) (min)	15	50	50	50	90
Running Time 3.0 AH (no load) (min)	-	-	-	-	105
Running Time 4.0 AH (no load) (min)	-	90	90	90	-
Running Time 6.0 AH (no load) (min)	-	117	117	117	-



EB518D



E522D





The EB518D hedge trimmer leads with comfort and durability. It's 18" blade length delivers great performance without the cost of a gas motor.



The E522D is light and balanced and has laser sharpened blades that will always create the perfect cut. It features a brushless motor and 22" blade length.


EB918D

SWIFT SERIES



This pole hedge trimmer cuts wide, high, and low hedges efficiently, thanks to a 6 position pivoting head.







Hadaa Tuimanan Coasifi aati ana	SWIFT	FLEX SERIES	
Hedge Trimmer Specifications	EB518D	EB918D	E522D
Voltage	40	40	40
Blade Length (in)	17.7"	18.1"	22"
Max Branch Thickness (in)	0.87"	0.94"	0.87"
Motor Power	Brushed	Brushed	Brushless
Net Weight (lbs)	6.4	7.7	7.1
Sound Power Level (dBA)	81.7	104	92
No Load Speed (rpm)	2600	1300	1300
Teeth Pitch (in)	0.87"	0.94"	0.87"
Cutting Diameter (in)	0.71"	0.79"	0.71"
Rotating Handle	90° (to left/ to right)	90° (to left/ to right)	90° (to left/ to right)
Running Time 2.0 AH (no load) (min)	60	60	40
Running Time 4.0 AH (no load) (min)	-	-	95
Running Time 6.0 AH (no load) (min)	-	-	140



	SWIFT	SERIES	RIES FLEX SERIES		PRO SERIES
Lawn Mower Specifications	EB132CP	E1B37CD	E137C	E142C	EA153V
Voltage (V)	40	40	40	40	120
Cutting Width (in)	12.6"	14.6"	15"	17"	20"
Cutting Height (in)	0.8"-2.4"	1"-3"	1"-3"	1"-2.75"	1"-3"
Capacity Grass Catcher (gal)	8	10.5	10.5	10.5	16
Motor Power	Brushed	Brushed	Brushless	Brushless	Brushless
No Load Speed (rpm)	3900	4000	4000	2800 / 3300	3300
Net Weight (lbs)	27.6	32	34.1	38.1	57.3
Sound Power Level (dBA)	96	96	96	96	96
Height Adjustment	5 stage	5 stage	5 stage	5 stage	7 stage
Wheel Size (front, rear) (in)	6" / 6"	6" / 6"	6" / 7"	6" / 7"	7" / 10"
Deck	Plastic	Plastic	Plastic	Steel	Steel
Drive Type	Push	Push	Push	Push	Self-Propelled
Running Time 2.0 AH (no load) (min)	25	25	23	23	32
Running Time 3.0 AH (no load) (min)	-	1	1	1	38
Running Time 4.0 AH (no load) (min)	-	-	49	49	-
Running Time 6.0 AH (no load) (min)	-	-	94	94	-



EB132CP



A ton of tech in a tiny place; adjustable cutting height that provides a custom yard.



EB137CD



Easy to lift, hard to put down. A bigger cutting width, cutting height, and grass catcher than the EB132CP.



E137C



A brushless motor and wider cutting deck. It can last up to an hour and a half to handle any job.



E142C



Large wheels provide high traction and easy driving. Brushless motors and high torque for more power.



EA153V



A self-propelled mower that features a 20" cutting deck, 120V power, and a brushless motor.



E808T





Our cordless auger head is designed for drilling soil, ice, and even mixing paint. It is powered by a brushless motor.

	FLEX SERIES
Auger Head Specifications	E808T
Voltage (V)	40
Motor Power	Brushless
No Load Speed (rpm)	0-250
Battery Series	Flex
Running Time 2.0 AH (no load) (min)	31
Running Time 4.0 AH (no load) (min)	62
Running Time 6.0 AH (no load) (min)	132

E806C



The dual stainless steel-made earth auger blade has a cutting diameter of 6" and a cutting depth of close to a full foot.

E808C



The dual stainless steel-made ice auger blade has a cutting diameter of 8" and a cutting depth of over 30".

E805C



The dual stainless steel-made mixer blade has a diameter of 4.7" and a mixing capacity of 2.5 to 13 gallons.



Blade Specifications	E808C	E806C	E805C
Type	Ice Blade	Earth Drill	Mixer
Width (in)	8"	6"	4.72"
Cutting Depth (in)	31.49"	11.8"	-
Mixing Capacity (gal)	1	-	2.5 -13
Net Weight (lbs)	19.4	17.8	15.2



Battery & Charger Information













	SWIFT SERIES	FLEX SERIES		PRO SERIES		
Battery Specifications	EB20	EP 20	EP40	EP60	EA20	EA30
Battery Cell	Li-ion	Li-ion	Li-ion	Li-ion	Li-ion	Li-ion
Battery Power (Wh)	80	80	160	240	240	360
Battery Voltage (V)	40	40	40	40	120	120
Battery Capacity (Ah)	2	2	4	6	2	3
Power Indicator	Yes	Yes	Yes	Yes	Yes	Yes
Fast Charge	Yes	Yes	Yes	Yes	Yes	Yes
Charging Time (min)	240 min.	36	69	84	108 / 37	158 / 54
Net Weight (lbs)	1.5	1.98	2.86	3.85	3.96	4.19









	SWIFT SERIES	FLEX SERIES PRO		SERIES
Charger Specifications	EBCO5	EC50	EC130	EC440
Charging Indicator	Yes	Yes	Yes	Yes
Battery Models	EB20	EP 20/40/60	EA20/EA30	EA20/EA30
Net Weight (lbs)	0.3	2.2	2.86	3.08
Working Voltage (V)	100-240	120	120	120
Rated Power (W)	21	250	160	250
Charging Current (A)	0.5	5	1	3.5

40V Power Belt



Work like the professionals and make your tool even lighter by carrying the weight of the battery on your waist.





radback

INDOUATION IS OUR PASSION

Let's Get Social













@RedbackTools

800-876-3009 REDBACKTOOLS.COM