Tubing Cutters





2-IN-1 CLOSE QUARTERS AUTOFEED® CUTTER

- The RIDGID® Model 118 Close Quarters with AUTOFEED® operation is available with a ratchet handle to allow for easier cutting in tight, restricted spaces. With its rugged and compact design, the handle can be attached to the cutter and operated in ratchet steps as small as 10 degrees. This allows for fine indexing of the cutter to operate in tight spaces. The new ratchet handle allows more flexibility and mobility while keeping the AUTOFEED® features of the model 118 Cutter, which is designed to cut hard and soft copper, aluminum and brass.
- Featuring the 2-in-1 Close Quarters Cutter where the cutter can be used alone or with the ratchet handle, a light and ergonomic accessory to help use the cutter in tight and restricted spaces.
- Easy to use in hard-to-reach areas because the knob only needs to be tightened once.
- Adjustable to any size from 1/4" 1 1/8" (6-28 mm) OD.
- Tubing cutter comes with a spare E-3469 Cutter Wheel in knob.
- New football-shaped knob in the cutter.
- Ratchet handle also compatible with Model 101 tubing cutter.

Catalog	Model	Description	Capacity		Weight		Std. Pack
No.	No.		in.	mm	lb.	kg	Stu. Fack
32573	118	2-In-1 Close Quarters Quick-Feed Cutter with Ratchet Handle	¹ / ₄ - 1 ¹ / ₈	6 - 28	1 ¹ / ₁₆	0.48	1
86127		Close Quarters AUTOFEED® Cutter Only	1/4 - 1 1/8	6 - 28	5/8	0.26	6
32933		Ratchet Handle Only for 101 and 118 Tubing Cutter	-	-			1



CONSTANT SWING TUBING CUTTERS

- Features an enclosed feed screw to eliminate clogging and jamming, grooved rollers for close-to-flare cuts, and a fold-away reamer.
- X-CEL® Knob cuts tubing more quickly and easily with our larger, more ergonomic designs.
- X-CEL Wheel Pin changes your cutter wheel quickly using a new ball detent design...no tool needed...no lost clips!
- Spare cutter wheel included in the knob.
- Made from high-strength zinc alloy.
- Cuts copper, brass, and aluminum tubing and thin-wall conduit.

Catalog	Model	Description	Std. Wheel	Capacity		Weight		Std. Pack
No.	No.	Description	Stu. Wileei	in.	mm	lb.	kg	Stu. Fack
31622	150	Constant Swing Cutter	E-3469	1/2 11/2	3 - 28	1	0.44	6
31627	130	Above w/H-D Wheel(s)	E-4546	'/8 - '/8				
66737	150-L	Constant Swing Cutter	E-3469	1/4 - 11/8	6 25	1 1/8	0.47	
66742	150-LS	Above with Heavy Duty Wheel	E-4546		6 - 35	1 '/8		

Tubing Cutters



ENCLOSED FEED TUBING CUTTERS

- Features an enclosed feed screw to eliminate clogging and jamming.
- X-CEL® Knob cuts tubing more quickly and easily with a larger, more ergonomic design.
- X-CEL Wheel Pin changes your cutter wheel quickly using a new ball detent design...no tool needed... no lost clips!
- Grooved rollers for close-to-flare cuts.
- Spare cutter wheel included in the knob.
- Fold-away reamer.
- · Made from high-strength zinc alloy.
- Cuts hard / soft copper, aluminum, brass and multilayer tubes.

Catalog	Model	Ctd W/		Capacity		Weight		Ctd Dook
No.	No.	Description	Std. Wheel	in.	mm	lb.	kg	Std. Pack
33055	205	Ratcheting Encl. Feed Cutter	E-3469	1/4 - 2 3/8	6 - 60	2	0.91	1
33070	205S	Above with Heavy Duty Wheel	E-4546	1/4 - 2 3/8	6 - 60	2		

*33070 is suitable for Stainless Steel.



X-CEL Pin = quicker wheel change

OUICK-ACTING TUBING CUTTERS

- Models 151-156 feature a quick-acting design, I-beam construction, hardened wear surfaces and thrust bearing slide assemblies for smooth operation.
- X-CEL® Knob cuts tubing more quickly and easily with a larger, more ergonomic designs.
- X-CEL Wheel Pin changes your cutter wheel quickly using a new ball detent design... no tool needed... no lost clips!
- Available in models for plastic pipe or metallic tubing.
- Models 151 and 152 feature fold-away reamers.
- · Model 151-ML is suitable for cutting multilayer tubing.

Catalog	Model No. Description Sto	Std. Wheel	Capa	Capacity		Weight		
No.	Model No.	Description	Stu. Wileei	in.	mm	lb.	kg	Std. Pack
31632	151	Quick-Acting Cutter	E-3469	1/4 - 15/8	6 - 42	1 1/4	0.56	6
31637	151-P	Above w/Wheel For Plastic	E-2155	1/8 - 11/4	10 - 40	1 '/4	0.00	
66747	151-ML	Quick-Acting Tubing Cutter	E-545	1/8 - 11/2	3 - 40	1	0.5	1
32078	151 CSST	Quick Acting CSST Cutter	E-4546	3/ ₈ - 1	10 - 25	1 ¹ / ₁₀	0.5	6
31642	152	Quick-Acting Cutter	E-3469	1/4 - 25/8	6 - 66		0.92	
31647	152-P	Above w/Wheel For Plastic	E-2155	1/4 - 2	10 - 63	2		
36597	153	Quick-Acting Cutter	E-3469	1 ¹ /4 - 3 ¹ /2	32 - 90			
36592	153-P	Above w/Wheel For Plastic	E-2155	1 - 3	25 - 75			
31652	154	Quick-Acting Cutter	E-2558	17/8 - 4 1/2	48 - 116	3 7/8	1.72	
31657	154-P	Above w/Wheel For Plastic	E-2156	1 <mark>1/2</mark> - 4	50 - 110	J'/8	1.72	
31662	156	Quick-Acting Cutter	E-2558	4 - 6 ⁵ /8	100 - 170	- 5	2.23	
31667	156-P	Above w/Wheel For Plastic	E-2157	4 - 6	110 - 160	υ	2.23	

^{*} Nominal plastic pipe size.

RIDGID® QUICK-ACTING PLASTIC CUTTER MODELS ARE EQUIPPED TO EASILY CONVERT TO CUT COPPER OR OTHER METALLIC TUBING.

- 1. Remove spare copper cutting wheel from knob.
- 2. Reverse knob position so that the "Cu" notation is visible inside the knob.
- 3. Screw knob back on to handle.
- 4. Using the X-CEL Wheel Pin, you can quickly replace the existing plastic cutting wheel with the copper cutting wheel. You're now ready to cut copper, aluminum, and brass tubing.
- 5. When you wish to revert to plastic cutting, follow the same instructions but make sure to reposition knob so that "PE" and "PVC" notations are visible inside knob.

Tubing Cutters



SCREW FEED TUBING CUTTERS

- Clean, square cuts are easily made on copper, brass, aluminum and thin-wall steel.
- X-CEL® Knob cuts tubing more quickly and easily with a larger, more ergonomic designs.
- Models 10, 15 and 20 feature a convenient fold-away reamer.

Catalog			Capa	acity	We	ight	Std. Pack	
No.	No.	Description	Stu. Wileei	in.	mm	lb.	kg	otu. i ack
32910	10	Tubing and Conduit Cutter	F-158	1/8 - 1	3 - 25	7/8	0.4	- 6
32915	10	Above w/H-D Wheel	E-1240	1/8 - 1	3 - 25	*/8		
32920	15	Tubing and Conduit Cutter	F-158	3/ ₁₆ - 11/ ₈	5 - 28	1/-	0.68	
32925	10	Above w/H-D Wheel	E-1240	³ / ₁₆ - 1 ¹ / ₈	5 - 28	1/2		
32930	20	Tubing and Conduit Cutter	F-158	⁵ /8 - 2 ¹ /8	16 - 54	13/4	0.79	
32935	20	Above w/H-D Wheel	E-1240	5/8 - 21/8	16 - 54	17/4	0.79	
32940	20	Tubing and Conduit Cutter	E-2558	1 - 3 ¹ / ₈	25 - 79	31/2	1.6	ı
32950	30	Above w/H-D Wheel (for steel)	E-2191	1 - 3 1/8	25 - 79	J'/2	1.0	



STAINLESS STEEL TUBING CUTTERS

- These tubing cutters have been designed for optimized performance on Stainless Steel tube.
- A contoured frame allows for easy alignment while adjusting the cutter to make a cut.
- Ergonomic knob allows for easy adjustments.
- Now includes X-CEL® Knob for quicker cutting.
- Six individual bearings in the 15-SI and 35S and 12 in the 65S replace traditional rollers. The bearings create a smoother cut, and allow for increased speed around the tube.
- Specially designed Stainless Steel cutter wheel in 35S and 65S contains bearings in the hub, to decrease drag around the tube for a smoother cut.

Catalog	Model	Description	Std.	Cap	acity	We	ight	Std.
No.	No.	Description	Wheel	in.	mm	lb.	kg	Pack
97212	15-SI	Stainless Steel Tubing & Conduit Cutter	E-1525	3/ ₁₆ - 1 ^{1/} ₈	5.0 - 28.0	11/2	0.68	
29963	35S	Stainless Steel Tubing Cutter	E-635	1/4 - 13/8	6.0 - 35.0	7/8	0.4	1
31803	65S	Stainless Steel Quick-Acting Tubing Cutter	E-635	1/4 - 25/8	6.0 - 67.0	11/2	0.68	
32078	151 CSST	Quick Acting CSST Cutter	E-4546	3/ ₈ - 1	10.0 - 25.0	1 ¹ /10	0.5	6
29973	E635	Stainless Steel Cutter Wheel with Bearings	-	-	-	1/32	0.01	1



INTERNAL TUBING CUTTERS

- For trimming tubing below floor level for shower/floor drain installations, or above the ceiling for sprinkler head installations.
- Model 106 features a tool steel and aluminum body while 108 and 109P have cast iron bodies.
- Each model features hardened steel rollers and cutter wheels.
- Model 109P is equipped to cut PVC or ABS plastic.

Catalog No.	Model	Description	Std. Wheel	Capa	acity	We	ight	Std. Pack	
	No.	No.	Description	Stu. Wileei	in.	mm	lb.	kg	olu. Fack
3	33005	106	Internal Cutter	E-2558	2 - 3	50 - 75	2 ³ /8	1.1	
8	83240	108	illerial Gutter	E-2558	1¼ - 2	32 - 50	2	0.9	-1
8	33290	109	2-Handle Internal Cutter	E-2558	2½ - 4	60 - 100	4	10	1
8	33295	109-P	Above w/Wheel for Plastic	E-5299	2¼ - 4	60 - 100	4	1.8	