



▲ Designate proper finish suffix





see what Delta can do



- H<sub>2</sub>Okinetic<sup>®</sup> 2-In-1 Shower
- 5-Spray Setting Hand Shower
- Certified Dual Check Valves

### **FEATURES:**

- Touch-Clean<sup>®</sup> Spray Holes
   H<sub>2</sub>Okinetic<sup>®</sup> PowerDrench Spray
- Push Button Selection
- MagnaTite<sup>®</sup> Docking
- Lumicoat<sup>®</sup> Finish (-PR models only)
- Lumicoat<sup>®</sup> Finishes easily wipe clean without cleaners and chemicals on the products most commonly touched areas

#### **STANDARD SPECIFICATIONS:**

- Max. flow rate 1.75 gpm at 80 psi, 6.6 L/min @ 550 kPa (58474-▲ and 58474-▲-PR)
- Max. flow rate 2.5 gpm at 80 psi, 9.5 L/min @ 550 kPa (58474-▲25 and 58474-▲-PR25)
- · Certified dual check valves for backflow prevention
- Integrated hand shower docks securely into showerhead when not in use
- 3-way diverter for extra spray options
- Fixed shower head and handshower all in one
- Hand held shower with 5 spray settings - pause is a non-positive shut-off
- Change spray modes with push button
- 60"-82" (1524 mm 2083 mm) stretchable metal hose
- Ball connector swivel angle is 30° (15° per side)
  Lumicoat<sup>®</sup> is not applied to the shower hose
- 5 Spray settings include: H<sub>2</sub>OKinetic<sup>®</sup> spray, H<sub>2</sub>OKinetic<sup>®</sup> spray with Massage, Massaging spray, and Pause

## **WARRANTY:**

- Parts and Finish Lifetime limited warranty; or for commercial purchasers, 10 years for multi-family residential (apartments and condominiums) and 5 years for all other commercial uses, in each case from the date the product is received by the original purchaser or their authorized representative (installation contractor, etc.).
- Please go to www.deltafaucet.com for the complete details of our limited warranty.



### **COMPLIES WITH:**

- ASME A112.18.1 / CSA B125.1◆
- ASME A112.18.3◆
- EPA WaterSense  $^{\circledR}$  Applies to 58474-  $\blacktriangle\&$ 58474-▲-PR
- ◆Your Delta hand shower incorporates a backflow protection system that has been tested to be in compliance with ASME A112.18.3 and ASME A112.18.1/ CSA B125.1. It incorporates two certified check valves in series, which operate independently and are integral, non-serviceable parts of the wand assembly.

# **Delta Faucet Company**

55 E. 111th Street, Carmel, IN 46280 350 South Edgeware Road, St. Thomas, ON N5P 4L1 © 2025 Delta Faucet Company