

Grinding Wheels

1



- For metal polishing & general flat grinding
- Aluminum oxide abrasive grains are evenly distributed to give a smooth surface

- For surfacing & grinding masonry



Diameter	Thickness	Arbor Hole	Grit	Max. Safe RPM	1/Pkg. Part #	5/Pkg. Part #	10/Pkg. Part #	25/Pkg. Part #	Model
General Purpose Metal Depressed Center Wheels									
4"	3/16"	5/8"	24	13,690	741402-B-1	741402-8		741402-B-25	9553NB, GA4030/K
4"	1/4"	5/8"	24	13,700	741402-9-1	741402-9AP		741402-C-25	
4"	3/16"	5/8"	36	13,690	741405-2-1	741405-2P			
4-1/2"	1/4"	7/8"	24	11,900	741423-0-1	741423-0		741423-B-25	9554NB, 9557NB/PB, 9564CV/PC, GA4530, GA4534
4-1/2"	1/4"	7/8"	36	11,900	741424-B-1	741424-8			9005B, 9015A, 9558PB, 9565CV/PC, GA5010Z, GA5020/Y
5"	1/4"	7/8"	24	11,000	741407-B-1			741407-B-25	9566CV/PC, GA6010Z, GA6020
6"	1/4"	7/8"	36	11,000	A-80846				GA7001L, GA7011C, GA7020, GA7021, GA7040S
7"	1/4"	7/8"	24	8,500	741413-3		741413-B-10		GA9020, GA9040S
9"	1/4"	7/8"	24	6,600			741421-B-10		
Hubbed General Purpose Metal Wheels									
4-1/2"	1/4"	5/8"-11	24	11,900			741416-B-10		9554NB, 9557NB/PB, 9564CV/PC, GA4530, GA4534
5"	1/4"	5/8"-11	24	11,000			741417-B-10		9005B, 9015A, 9558PB, 9565CV/PC, GA5010Z, GA5020/Y, GA6020
7"	1/4"	5/8"-11	24	8,500			741414-B-10		GA7001L, GA7011C, GA7020, GA7021, GA7040S
9"	1/4"	5/8"-11	24	6,600			741415-B-10		GA9020, GA9040S
Masonry Depressed Center Wheels									
4"	1/4"	5/8"	24	13,700			741425-B-25		9553NB, GA4030/K
4-1/2"	1/4"	7/8"	24	11,900			741426-B-25		9554NB, 9557NB/PB, 9564CV/PC, GA4530, GA4534
5"	1/4"	7/8"	24	11,000			741427-B-25		9005B, 9015A, 9558PB, 9565CV/PC, GA5010Z, GA5020/Y, GA6020
Hubbed Masonry Depressed Center Wheels									
7"	1/4"	5/8"-11	24	8,500			741428-B-10		GA7001L, GA7011C, GA7020, GA7021, GA7040S
9"	1/4"	5/8"-11	24	6,600			741429-B-10		GA9020, GA9040S

Flex & Cut-Off Wheels

2



- Most versatile wheel for light metal grinding, sanding and cutting
- Use with Plastic Back-up Pad *743009-1A

3



- For all ferrous materials steel & cast iron
- For masonry/concrete, marble, slate & more
- *Bulk must be ordered in shelf pack quantity

3



- Cuts up to 50% faster
- Lasts up to 20% longer
- Use with paper flange (included)

Diameter	Thickness	Arbor Hole	Grit	Max. Safe RPM	10/Pkg. Part #	Model			
Depressed Center Flex Wheels									
4"	1/8"	5/8"	AC46	13,700	741404-0BP*	9553NB, GA4030/K			
4"	1/8"	5/8"	AC60	13,700	741404-0CP*				
4"	1/8"	5/8"	GC60	13,690					
4"	1/8"	5/8"	AC80	13,700	741404-0DP*				
4"	1/8"	5/8"	AC120	13,700	741404-0FP*				
Diameter	Thickness	Arbor Hole	Grit	Max. Safe RPM	Bulk Shelf * Pack Qty.	Metal Bulk * Part #	Metal 10/Pkg. Part #	Masonry 10/Pkg. Part #	Model
Cut-Off Wheels									
4"	3/32"	5/8"	A36P	13,600	25	A-90358*			9553NB, GA4030/K
4"	5/64"	5/8"	A46	14,000			724107-5-10		
4"	3/32"	5/8"	C36	15,000				724104-1-10	
Diameter	Thickness	Arbor Hole	Grit	Max. Safe RPM	Stainless 25/Pkg. Part #	Metal 25/Pkg. Part #	Model		
Super Thin Cut-Off Wheels									
4"	3/64"	5/8"	A46	15,280	724111-A-25	724114-A-25	9553NB, GA4030/K		
4-1/2"	3/64"	7/8"	A46	13,285	724112-A-25	724115-A-25	9554NB, 9557NB/PB, 9564CV/PC, GA4530, GA4534		
5"	3/64"	7/8"	A46	12,200	724113-A-25	724116-A-25	9005B, 9015A, 9558PB, 9565CV/PC, GA5010Z, GA5020/Y		
6"	1/16"	7/8"	A46	10,185	724118-A-25	724117-A-25	9566CV/PC, GA6010Z, GA6020		

Warning: Consult owner/operator manual and adhere to all safety precautions for accessory items. Always use recommended guards. Failure to do so may result in serious injury or death from exploding wheels. Refer to ANSI B7.1 and owner/operator manual for proper accessory mounting and grinding procedures. Always wear eye protection that meets ANSI Z87.1 requirements plus a face shield wherever possible. Tools must always be properly guarded.