

Sanding / Polishing Pads & Bonnets

B	Description	Grinder/Polisher Size	Model	Part #
	Rubber Pad	4"	GA4030/K	743009-6
		4"	PW5001C	743079-5
		4-1/2"	9557NB/PB, 9564CV/P/PC, GA4530, GA4534 XAG01, XAG03, XAG06	743036-3
		5"	9005B/BZ, 9015A, 9565CV/PC, GA5010Z, GA5020/Y	743015-1
		6"	9566CV/PC, GA6010, GA6020	743016-9
		7", 9"	GA7001L, GA7911, GV7000C, 9077SL, 9218SB, 9227C, 9227CY, 9237C, GA7011C, GA7020, GA7021, GA7040S	192978-2
	Plastic Pad	5"	GV5000, GA5010	743025-8
	Hook-and-Loop Backing Pad	7"	9227C/CY, 9237C, PV7001C	743052-5

C	Description	Grinder/Polisher Size	Model	Part #
   	7" Wool Bonnet Tie Back	7"	9227C/CY, 9237C, PV7001C	794176-0
	7" Hook-and-Loop Pad Compounding	7"	9227C/CY, 9237C, PV7001C	192629-7
	7" Hook-and-Loop Pad Polishing	7"	9227C/CY, 9237C, PV7001C	743403-A
	7-1/2" Hook-and-Loop Foam Pad Polishing	7"	9227C/CY, 9237C, PV7001C	193470-1

C Wire Brushes

C	Description	Diameter	Arbor	Max. RPM	Model	Carbon Steel Part #	Stainless Steel Part #
	Crimped Cup • Excellent for flat surfaces, edges, paint, scale, light rust removal • Use with spindle mount washer (261039-0)	3"	M10 x 1.25	14,000	GA4030	743201-4	
		3"	5/8" - 11	14,000	9005B/BZ, 9557NB/PB, 9558PB, 9564CV/PC, 9565CV/PC, GA4530, GA4534, GA5010Z, GA5020/Y	743205-6	
		4"	5/8" - 11	10,000	9566CV, GA7001L, GA7011C, GA7040S	743207-2	
		6"	5/8" - 11	6,600	GA7001L, GA7011C, GA7020, GA7021, GA9020, GA9040S	743206-B	
	Knot Cup • Ideal for tight operations, corners and angle welds • Rugged knot construction • .020" Type 302 stainless steel wire is corrosion resistant • Use with spindle mount washer (261039-0)	2-3/4"	M10 X 1.25	14,000	GA4030	743201-5A	743204-A
		2-3/4"	5/8" - 11	14,000	9005B/BZ, 9557NB/PB, 9558PB, 9564CV/PC, 9565CV/PC, GA4530, GA4534, GA5010Z, GA5020/Y	743209-A	743209-B
		4"	5/8" - 11	10,000	9564CV/PC/P, 9565CV/PC, 9566CV/PC, GA7001L, GA7011C, GA7020, GA7021, GA7040S	743208-0A	
		6"	5/8" - 11	6,600	GA7001L, GA7011C, GA7020, GA7021, GA9020, GA9040S, GA9040S	743206-A	

C Wire Wheels

C	Description	Diameter	Arbor	Max. RPM	Model	Carbon Steel Part #	Stainless Steel Part #
	Stringer Bead Twist Wheel • 3/16" face width for stringer weld, piping, pipe grooves, and hard to reach areas • .020" Type 302 stainless steel wire is highly corrosion resistant	4"	M10 x 1.25	20,000	GA4030	743203-5A	743204-B
		4"	5/8" - 11	20,000	9005B/BZ, 9557NB/PB, 9558PB, GA4530, GA4534, GA5010Z, GA5020/Y	743213-A	743213-B
		5"	5/8" - 11	12,500	9005B/BZ, 9557NB/PB, 9558PB, GA7001L, GA7011C, GA7020/21, GA9020, GA9040S	743216-A	
	Knot Full Cable Twist Wheel • 1/4" face width for narrow to medium width work, excellent for cleaning welds • .020" Type 302 stainless steel wire is highly corrosion resistant	4"	M10 X 1.25	20,000	GA4030		743203-4B
		4"	5/8" - 11	20,000	9564CV/PC/P, 9565CV/PC, 9566CV/PC, GA7001L, GA7011C, GA7020, GA7021, GA7040S	743211-A	743214-A
		5"	5/8" - 11	12,500	9564CV/PC/P, 9565CV/PC, 9566CV/PC, GA7001L, GA7011C, GA7020, GA7021, GA7040S	743217-A	
		6"	5/8" - 11	12,500	GA7001L, GA7011C, GA7020, GA7021, GA7040S, GA9020, GA9040S	743218-A	
	Knot Standard Twist Wheel • 1/2" face width for broader cleaning coverage. For deburring, edge blending & finishing. • Removes rust, scale, and weld splatter	4"	M10 X 1.25	20,000	GA4030	743203-4C	
		4"	5/8" - 11	20,000	9005B/BZ, 9557NB/PB, 9558PB, GA4530, GA4534	743212-A	

Small Angle Grinder Adapters

Allows cup or wheel with 5/8"-11 arbors to fit M10 x 1.25 arbors

Part #

323015-A

Allows cup or wheel with 5/8"-11 arbors to fit M10 x 1.50 arbors

323016-A

Warning: Consult owner/operator manual and adhere to all safety precautions for accessory items. Always use recommended guards. Failure to do so may result in serious injury or death from exploding wheels. Refer to ANSI B7.1 and owner/operator manual for proper accessory mounting and grinding procedures. Always wear eye protection that meets ANSI Z87.1 requirements plus a face shield wherever possible. Tools must always be properly guarded.